



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Arita Flow Control (Tianjin) Co.,Ltd

No.11 Nan Caiyuan Road, Wuqing Development Area,
Tianjin, China 301701

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland
CMI Certification Pty Ltd
PO Box 273, Palmwoods, Qld 4555, Australia
ABN: 81 663 250 815
T: + 61 7 5445 2199
W: www.cmicert.com.au
E: office@cmicert.com.au



080089	17/12/2024	17/12/2024	16/12/2029	WMTS-012:2018 In-line valves for use in plumbing water supply systems – Miscellaneous types metallic and non-metallic
--------	------------	------------	------------	---

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Arita Flow Control (Tianjin) Co.,Ltd



APPLICABLE
STANDARD/SPECIFICATION
WMTS-012:2018 In-line valves for use in plumbing water supply systems
– Miscellaneous types metallic and non-metallic

Brand Name	Model Identification	Product Description	Metallic Materials	Non-Metallic Materials	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
ARITA	CBV-WM-G-LUG-050	BUTTERFLY VALVE - CI LUG TE 2' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-065	BUTTERFLY VALVE - CI LUG TE 2 1/2' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-080	BUTTERFLY VALVE - CI LUG TE 3' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-100	BUTTERFLY VALVE - CI LUG TE 4' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-125	BUTTERFLY VALVE - CI LUG TE 5' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-150	BUTTERFLY VALVE - CI LUG TE 6' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-200	BUTTERFLY VALVE - CI LUG TE 8' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-250	BUTTERFLY VALVE - CI LUG TE 10' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-LUG-300	BUTTERFLY VALVE - CI LUG TE 12' WM GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024

ARITA	CBV-WM-L-LUG-050	BUTTERFLY VALVE - CI LUG TE 2' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-065	BUTTERFLY VALVE - CI LUG TE 2 1/2' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-080	BUTTERFLY VALVE - CI LUG TE 3' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-100	BUTTERFLY VALVE - CI LUG TE 4' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-125	BUTTERFLY VALVE - CI LUG TE 5' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-150	BUTTERFLY VALVE - CI LUG TE 6' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-200	BUTTERFLY VALVE - CI LUG TE 8' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-250	BUTTERFLY VALVE - CI LUG TE 10' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-LUG-300	BUTTERFLY VALVE - CI LUG TE 12' WM LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-050	BUTTERFLY VALVE - DI LUG TE 2' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-065	BUTTERFLY VALVE - DI LUG TE 2 1/2' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-080	BUTTERFLY VALVE - DI LUG TE 3' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-100	BUTTERFLY VALVE - DI LUG TE 4' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-125	BUTTERFLY VALVE - DI LUG TE 5' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-150	BUTTERFLY VALVE - DI LUG TE 6' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA	N/A	17/12/2024

					Max Working Temperature: 110°C		
ARITA	DBV-WM-G-LUG-200	BUTTERFLY VALVE - DI LUG TE 8' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-250	BUTTERFLY VALVE - DI LUG TE 10' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-LUG-300	BUTTERFLY VALVE - DI LUG TE 12' WM GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-050	BUTTERFLY VALVE - DI LUG TE 2' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-065	BUTTERFLY VALVE - DI LUG TE 2 1/2' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-080	BUTTERFLY VALVE - DI LUG TE 3' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-100	BUTTERFLY VALVE - DI LUG TE 4' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-125	BUTTERFLY VALVE - DI LUG TE 5' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-150	BUTTERFLY VALVE - DI LUG TE 6' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-200	BUTTERFLY VALVE - DI LUG TE 8' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-250	BUTTERFLY VALVE - DI LUG TE 10' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-LUG-300	BUTTERFLY VALVE - DI LUG TE 12' WM LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-050	BUTTERFLY VALVE - CI WAFER WM 2' GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-065	BUTTERFLY VALVE - CI WAFER WM 2 1/2' GEAR PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPA Max Working Temperature: 110°C	N/A	17/12/2024

ARITA	CBV-WM-G-W-080	BUTTERFLY VALVE - CI WAFER WM 3' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-100	BUTTERFLY VALVE - CI WAFER WM 4' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-125	BUTTERFLY VALVE - CI WAFER WM 5' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-150	BUTTERFLY VALVE - CI WAFER WM 6' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-200	BUTTERFLY VALVE - CI WAFER WM 8' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-250	BUTTERFLY VALVE - CI WAFER WM 10' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-G-W-300	BUTTERFLY VALVE - CI WAFER WM 12' GEAR PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-050	BUTTERFLY VALVE - CI WAFER WM 2' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-065	BUTTERFLY VALVE - CI WAFER WM 2 1/2' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-080	BUTTERFLY VALVE - CI WAFER WM 3' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-100	BUTTERFLY VALVE - CI WAFER WM 4' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-125	BUTTERFLY VALVE - CI WAFER WM 5' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-150	BUTTERFLY VALVE - CI WAFER WM 6' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-200	BUTTERFLY VALVE - CI WAFER WM 8' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	CBV-WM-L-W-250	BUTTERFLY VALVE - CI WAFER WM 10' LEVER PN16	Cl; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa	N/A	17/12/2024

					Max Working Temperature: 110°C		
ARITA	CBV-WM-L-W-300	BUTTERFLY VALVE - CI WAFER WM 12' LEVER PN16	CI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-050	BUTTERFLY VALVE - DI WAFER WM 2' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-065	BUTTERFLY VALVE - DI WAFER WM 2 1/2' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-080	BUTTERFLY VALVE - DI WAFER WM 3' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-100	BUTTERFLY VALVE - DI WAFER WM 4' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-125	BUTTERFLY VALVE - DI WAFER WM 5' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-150	BUTTERFLY VALVE - DI WAFER WM 6' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-200	BUTTERFLY VALVE - DI WAFER WM 8' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-250	BUTTERFLY VALVE - DI WAFER WM 10' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-G-W-300	BUTTERFLY VALVE - DI WAFER WM 12' GEAR PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-W-050	BUTTERFLY VALVE - DI WAFER WM 2' LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-W-065	BUTTERFLY VALVE - DI WAFER WM 2 1/2' LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-W-080	BUTTERFLY VALVE - DI WAFER WM 3' LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024
ARITA	DBV-WM-L-W-100	BUTTERFLY VALVE - DI WAFER WM 4' LEVER PN16	DI; SS416; CF8M; SS316	PTFE; EPDM	For Water Supply Use Max Working Pressure: 2.4MPa Max Working Temperature: 110°C	N/A	17/12/2024

~~~~~

|       |                |                                                 |                        |            |                                                                                        |     |            |
|-------|----------------|-------------------------------------------------|------------------------|------------|----------------------------------------------------------------------------------------|-----|------------|
| ARITA | DBV-WM-L-W-125 | BUTTERFLY VALVE - DI WAFER WM 5'<br>LEVER PN16  | DI; SS416; CF8M; SS316 | PTFE; EPDM | For Water Supply Use<br>Max Working Pressure: 2.4MPA<br>Max Working Temperature: 110°C | N/A | 17/12/2024 |
| ARITA | DBV-WM-L-W-150 | BUTTERFLY VALVE - DI WAFER WM 6'<br>LEVER PN16  | DI; SS416; CF8M; SS316 | PTFE; EPDM | For Water Supply Use<br>Max Working Pressure: 2.4MPA<br>Max Working Temperature: 110°C | N/A | 17/12/2024 |
| ARITA | DBV-WM-L-W-200 | BUTTERFLY VALVE - DI WAFER WM 8'<br>LEVER PN16  | DI; SS416; CF8M; SS316 | PTFE; EPDM | For Water Supply Use<br>Max Working Pressure: 2.4MPA<br>Max Working Temperature: 110°C | N/A | 17/12/2024 |
| ARITA | DBV-WM-L-W-250 | BUTTERFLY VALVE - DI WAFER WM 10'<br>LEVER PN16 | DI; SS416; CF8M; SS316 | PTFE; EPDM | For Water Supply Use<br>Max Working Pressure: 2.4MPA<br>Max Working Temperature: 110°C | N/A | 17/12/2024 |
| ARITA | DBV-WM-L-W-300 | BUTTERFLY VALVE - DI WAFER WM 12'<br>LEVER PN16 | DI; SS416; CF8M; SS316 | PTFE; EPDM | For Water Supply Use<br>Max Working Pressure: 2.4MPA<br>Max Working Temperature: 110°C | N/A | 17/12/2024 |

\*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record