

Certification Body:


 ABN: 81 663 250 815
 JAS-ANZ Accreditation
 No. Z4450210AK
 PO Box 273,
 Palmwoods Qld 4555
 Australia
 P: +61 7 5445 2199
www.cmicert.com.au
office@cmicert.com.au

Certificate Holder:


 Ensystex Australasia
 Pty Ltd
 ABN: 53 102 221 965
 Warehouse D, Building
 6, The Switchyard
 161 Manchester Road
 Auburn NSW 2144
 Australia
 P: 13 35 36
www.trithor.com.au

Certificate number: CM40255

THIS IS TO CERTIFY THAT

TRITHOR Termite Protection

Type and/or use of product:

A termite management system used to deter concealed subterranean termite entry into buildings.

Description of product:

TRITHOR Termite Protection consists of an inner core layer that is impregnated with deltamethrin and laminated top and bottom with a LDPE plastic membrane.

COMPLIES WITH THE FOLLOWING BCA PROVISIONS AND STATE OR TERRITORY VARIATION(S)

BCA 2022

	Volume One	Volume Two
Performance Requirement(s):	Not Applicable	Not Applicable
Deemed-to-Satisfy Provision(s):	B1D4(i) Termite Risk Management F1D6(2)(b) Damp-proofing – Subject to <i>Limitation and Condition 9</i>	H1D3(3) Termite Management Systems H2D4(2)(c) Damp-proof courses and flashings – material– subject to <i>Limitation and Condition 9</i>
State or territory variation(s):	NT B1D4(i)	QLD H1D3(3)

SUBJECT TO THE FOLLOWING LIMITATIONS AND CONDITIONS AND THE PRODUCT TECHNICAL DATA IN APPENDIX A AND EVALUATION STATEMENTS IN APPENDIX B

Limitations and conditions:

- Only to be installed by persons accredited by the manufacturer and appropriately licensed in the relevant State or Territory.
- TRITHOR Termite Protection, must have the required inspection zones as outlined in the product technical manual (listed below).
- Inspections must be undertaken annually as outlined in the [TRITHOR Termite Protection Technical Manual 8.05](#) to assist with identifying any activity that may result in the bridging or breaching of the system.
- A durable notice must be installed in accordance with BCA Volume One 2022: B1D4(i), & Part 3.4.3 of the ABCB Housing Provisions including State variations.
- Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
- This Certificate is issued based on the evidence of compliance as detailed herein. Any deviation from the specifications contained in this Certificate is outside of this document's scope and the installation of the certified product/system will not be covered by this CodeMark certification. This may result in the product being classified as a non-conforming building product/system.

Building classification/s:

Class 1,2,3,4,5,6,7,8,9 & 10


 Glen Gugliotti – CMI


 Don Grehan – Unrestricted Building Certifier

Date of issue: 23/01/2025

Date of expiry: 25/01/2028



Certificate of Conformity

7. The use of the certified product/system is subject to these Limitations and Conditions and must be read in conjunction with the Scope of Certification below.
8. The installation of any termite management system cannot guarantee 100% protection against infestation by subterranean termites. Thus, the installation of a system does not negate the need for regular competent inspections. Any additions, alterations, or earth works, including gardening adjacent to the building, may render the system ineffective. Such activity should be referred to a licensed installation contractor for appropriate advice and treatment.
9. When TRITHOR Termite Protection is used as a damp-proof course or flashing, it must be continuous through the wall or pier with no penetration of the material.
10. Any additional treatment should be done in accordance with the relevant State or Territory regulations.

Scope of certification: The CodeMark Scheme is a building product certification scheme. The rules of the Scheme are available at the ABCB website www.abcb.gov.au. This Certificate of Conformity is to confirm that the relevant requirements of the Building Code of Australia (BCA) as claimed against have been met. The responsibility for the product performance and its fitness for the intended use remain with the Certificate Holder. The certification is not transferrable to a manufacturer not listed on Appendix A of this certificate.

Only criteria as identified within this Certificate of Conformity can be used for CodeMark certification claims. Where other claims are made in a client's Installation Manual, Website or other documents that are outside the criteria on this Certificate of Conformity, such criteria cannot be used or claimed to meet the requirements of this CodeMark certification.

The NCC defines a Performance Solution as one that complies with the Performance Requirements by means other than a Deemed-to-Satisfy Solution. A Building Solution that relies on a CodeMark Certificate of Conformity that certifies a product against the Performance Requirements cannot be considered as Deemed-to-Satisfy Solution.

This Certificate of Conformity may only relate to a part of a Performance Solution. In these circumstances other evidence of suitability is needed to demonstrate that the relevant Performance Requirements have been met. The relevant provisions of the Governing Requirements in Part A of the NCC will also need to be satisfied.

This Certificate of Conformity is issued based on the evidence of compliance as detailed herein. Any deviation from the specifications contained in this Certificate of Conformity is outside of this document's scope and the installation of the certified product will not be covered by this Certificate of Conformity.

Disclaimer: The Scheme Owner, Scheme Administrator and Scheme Accreditation Body do not make any representations, warranties or guarantees, and accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of any material contained within this certificate; and the Scheme Owner, Scheme Administrator and Scheme Accreditation Body disclaim to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this certificate.

When using the CodeMark logo in relation to or on the product/system, the Certificate Holder makes a declaration of compliance with the Scope of Certification and confirms that the product is identical to the product certified herein. In issuing this Certificate of Conformity, CMI Certification Pty Ltd (CMI) has relied on the experience and expertise of external bodies (laboratories and technical experts).

Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.

APPENDIX A – PRODUCT TECHNICAL DATA

A1 Type and intended use of product

As per page 1.

A2 Description of product

As per page 1.

A3 Product specification

Trithor Sheet: A 50-metre (+/- 500mm) roll of sheet material with a thickness of 0.80–0.95mm. The sheet features an inner core layer impregnated with 1g of Deltamethrin per square metre, laminated with a Blue upper layer and a Yellow Bottom/Outer layer made of LDPE plastic membrane. Available in the following roll widths:

- 1500mm +/- 20mm
- 600mm +/- 20mm
- 500mm +/- 20mm
- 300mm +/- 20mm
- 350mm +/- 20mm
- 250mm +/- 20mm
- 200mm +/- 20mm
- 150mm +/- 20mm
- 100mm +/- 20mm
- 75mm +/- 20mm

60mm Collars: These are formed from the Trithor Sheets. Each consists of:

- 300mm +/- 10mm square with a 60mm +/- 5 mm hole cut in the centre.
- 100mm long tube formed with an internal diameter of 60mm +/- 5mm.

120mm Collars: These are formed from Trithor Sheets. Each consists of:

- 300mm +/- 10 mm square with a 120mm +/- 5mm hole cut in the centre.
- 100mm long tube formed with an internal diameter of 120mm +/- 5mm.

Internal Corners: These are formed from Trithor Sheets.

External Corners: These are formed from Trithor Sheets.

Tubes: These are formed from Trithor Sheets. Each consists of:

- 300mm long tube formed with an internal diameter of 60mm +/- 5mm.

Patches: These are formed from Trithor Sheets.

Adhesive Spray: TRITHOR MAXX Termiticidal Contact Adhesive Spray containing 1.3g/kg Bifenthrin.

If unavailable:

3M Multi-purpose Adhesive, 3M Super 77 Spray Adhesive, or 3M Foam Fast 74 Spray Adhesive are acceptable alternatives.

If these are also unavailable:

Garrards Pre-Con 10 Termite Barrier Adhesive.

Certificate of Conformity

A4 Manufacturer and manufacturing plant(s)

This field is optional. Contact the Certificate Holder for details.

A5 Installation requirements

The TRITHOR Termite Protection system must be installed in accordance with the [TRITHOR Termite Protection Technical Manual 8.05](#).

When used in conjunction with a concrete slab, the slab must be constructed in accordance with the requirements of AS 2870-2011 Residential slabs and footings or AS 3600-2018 Concrete Structures (Amendment No.1 and No.2).

A6 Other relevant technical data

No other relevant technical data.

APPENDIX B – EVALUATION STATEMENTS

B1 Evaluation methods

1. Termite Management Provisions – A5G3(1)(e). Reports from a professional engineer or other appropriately qualified persons.
2. Damp-Proofing Provisions – A5G3(1)(e). Reports from a professional engineer or other appropriately qualified persons.

B2 Reports

1. Australian Pesticides and Veterinary Management Authority (APVMA); Approval 59139 & 82052. This document contributes towards compliance with B1D4 & H1D3.
2. Australian Timber & Pest Research Pty Ltd; Trithor Compliance with NCC Statement; Compliance with NCC Volume 1 Clause B1.4(i) & NT B1.4(i), F1.9(b)(ii), & NCC Volume 2 Clause 3.1.4.3(b)(i)(ii) & QLD 3.1.4.3(b)(i)(ii), 3.3.5.7(e); Dated 19/01/2023. This document shows compliance with B1D4, H1D3, F1D6 & H2D4.
3. Consulting New South Wales; University of New South Wales; Opinion on Inspection Zones.

The Certificate Holder has chosen not to make the above evidence of compliance publicly available, due to the documents being considered commercial in confidence.