



CMI ProdCert
PC10291

CERTIFICATE OF CONFORMITY

This is to certify that

Finwood (AUST) Pty Ltd

Is certified to manufacture products to:

AS/NZS 4357.0:2022 Structural laminated veneer lumber - Specifications

Certificate Holder

Finwood (AUST) Pty Ltd
11 Delawney Street, Balcatta, WA 6021,
Australia
ABN: 95 689 918 616

Product Description

Laminated Veneer Lumber (LVL)

Product Purpose or Use

Laminated Veneer Lumber (LVL)

Subject to the following Conditions & Limitations:

Nil

Certificate No: PC10291

Originally Certified: 01/09/2026

Updated: 01/09/2026

Expires: 01/09/2031

Talissa Ireland
CMI Certification Pty Ltd



CMI Certification Pty Ltd
ABN: 81 663 250 815
JAS-ANZ Accreditation No.
Z4450210AK
PO Box 273, Palmwoods Qld 4555,
Australia
Ph: +61 7 5445 2199
E: office@cmicert.com.au
W: <https://cmicert.com.au/>



- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



CERTIFICATE OF CONFORMITY

This is to certify that

Finwood (AUST) Pty Ltd

Is certified to manufacture products to:

AS/NZS 4357.0:2022 Structural laminated veneer lumber - Specifications

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 27 – Thickness: 45mm - Width: 90mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	90x45 LVL 14 F17	General Structural Use	F17	A	Phenolic Formaldehyde Resin	-	E ₀	17617	82.9	6.3	13.0	-	14627	80.0	5.5	6.0	-	55.1	50.5	19/03/2026

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 37 – Thickness: 65mm - Width: 95mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	95x65 LVL 14 F17	General Beam Use on Edge Only	F17	A	Phenolic Formaldehyde Resin	-	E ₀	15949	76.4	6.6	10.2	-	-	-	-	-	-	-	-	19/03/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 44 – Thickness: 77mm - Width: 150mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f'_b [MPa]	On Edge f'_s [MPa]	On Edge f'_ρ [MPa]	On Edge f'_{sj} [MPa]	On Flat E [MPa]	On Flat f'_b [MPa]	On Flat f'_s [MPa]	On Flat f'_ρ [MPa]	On Flat f'_{sj} [MPa]	Axial f'_t [MPa]	Axial f'_c [MPa]	Date Endorsed
FINWOOD	150x77 LVL 14 F17	General Beam Use on Edge Only	F17	A	Phenolic Formaldehyde Resin	-	E ₀	15158	68.7	5.5	9.2	-	-	-	-	-	-	-	-	19/03/2026

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 22 – Thickness: 35mm - Width: 90mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_ρ' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_ρ' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	90x35 LVL 14 F17	General Structural Use	F17	A	Phenolic Formaldehyde Resin	-	E ₀	14416	54.9	5.2	10.1	-	14020	69.8	4.8	1.7	-	36.1	36.0	19/03/2026

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 28 – Thickness: 45mm - Width: 240mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_ρ' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_ρ' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	240x45 LVL 14 F17	General Structural Use	F17	A	Phenolic Formaldehyde Resin	-	E ₀	15552	60.8	-	-	-	14329	64.3	-	-	-	-	-	19/03/2026

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 28 – Thickness: 45mm - Width: 300mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_ρ' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_ρ' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	300x45 LVL 14 F17	General Structural Use	F17	A	Phenolic Formaldehyde Resin	-	E ₀	14572	66.1	5.1	10.0	-	14978	73.6	4.6	4.5	-	27.7	32.6	19/03/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>

Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 19 – Thickness: 35mm - Width: 90mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f'_b [MPa]	On Edge f'_s [MPa]	On Edge f'_p [MPa]	On Edge f'_{sj} [MPa]	On Flat E [MPa]	On Flat f'_b [MPa]	On Flat f'_s [MPa]	On Flat f'_p [MPa]	On Flat f'_{sj} [MPa]	Axial f'_t [MPa]	Axial f'_c [MPa]	Date Endorsed	
FINWOOD	90x35 LVL 13 E13/F14	General Structural Use	E13 F14	A	Phenolic Formaldehyde Resin	-	Super E ₀	13100	71.0	6.0	13.1	-	16274	77.8	6.7	9.5	-	37.4	38.8	19/03/2026	
								Nails				Screws				Bolts					
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face			
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴			
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge							
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²							
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge							
								JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴							

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 19 – Thickness: 35mm - Width: 120mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed	
FINWOOD	120x35 LVL 13 E13/F14	General Beams Used on Edge Only	E13 F14	A	Phenolic Formaldehyde Resin	-	Super E ₀	13658	64.6	5.5	15.5	-	-	-	-	-	-	-	-	19/03/2026	
								Nails				Screws				Bolts					
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face			
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴			
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge							
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²							
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge							
								JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴							

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 23 – Thickness: 45mm - Width: 90mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed	
FINWOOD	90x45 LVL 13 E13/F14	General Structural Use	E13 F14	A	Phenolic Formaldehyde Resin	-	Super E ₀	15117	71.9	6.7	12.6	-	15453	69.4	5.2	11.1	-	36.0	40.3	19/03/2026	
								Nails				Screws				Bolts					
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face			
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴			
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge							
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²							
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge							
								JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴							

1.Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
 2.Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
 3.Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
 4.Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
 5.Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
 6.Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)

8.Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
 9.Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
 10.Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
 11.Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 100mm x Root Dia: 4.00mm)
 12.Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 100mm x Root Dia: 4.00mm)
 13.Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 23 – Thickness: 45mm - Width: 200mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed	
FINWOOD	200x45 LVL 13 E13	General Beams Used on Edge Only	E13	A	Phenolic Formaldehyde Resin	-	Super E ₀	13356	69.8	5.5	15.2	-	-	-	-	-	-	-	-	19/03/2026	
								Nails				Screws				Bolts					
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face			
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴			
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge							
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²							
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge							
								JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴							

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber - Wood Species: Larch – Plies: ≥ 33 – Thickness: 63mm - Width: 300mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed	
FINWOOD	300x63 LVL 13 E13	General Beams Used on Edge Only	E13	A	Phenolic Formaldehyde Resin	-	Super E ₀	13148	60.3	5.6	16.2	-	-	-	-	-	-	-	-	19/03/2026	
								Nails				Screws				Bolts					
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Perpendicular Face			
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴			
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge							
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²							
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge							
								JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴							

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 100mm x Root Dia: 4.00mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 100mm x Root Dia: 4.00mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber – Mixed Wood Species: Radiata Pine & Larch – Plies: ≥ 19 – Thickness: 35mm - Width: 90mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f'_b [MPa]	On Edge f'_s [MPa]	On Edge f'_p [MPa]	On Edge f'_{sj} [MPa]	On Flat E [MPa]	On Flat f'_b [MPa]	On Flat f'_s [MPa]	On Flat f'_p [MPa]	On Flat f'_{sj} [MPa]	Axial f'_t [MPa]	Axial f'_c [MPa]	Date Endorsed
FINWOOD	90x35 LVL 10 F11	General Structural Use	F11	A	Phenolic Formaldehyde Resin	-	E ₀	13427	65.1	5.8	9.4	-	10722	55.6	4.9	6.7	-	36.2	35.5	19/03/2026
								Nails				Screws				Bolts				
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴		
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge						
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²						
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge						
JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴														

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 70mm x Dia: 3.00mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 70mm x Root Dia: 3.50mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber – Mixed Wood Species: Radiata Pine & Larch – Plies: ≥ 24 – Thickness: 45mm - Width: 90mm

Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f'_b [MPa]	On Edge f'_s [MPa]	On Edge f'_p [MPa]	On Edge f'_{sj} [MPa]	On Flat E [MPa]	On Flat f'_b [MPa]	On Flat f'_s [MPa]	On Flat f'_p [MPa]	On Flat f'_{sj} [MPa]	Axial f'_t [MPa]	Axial f'_c [MPa]	Date Endorsed
FINWOOD	90x45 LVL 10 F11	General Structural Use	F11	A	Phenolic Formaldehyde Resin	-	E ₀	14323	64.3	5.2	9.6	-	10847	59.1	6.3	7.2	-	33.7	38.9	19/03/2026
								Nails				Screws				Bolts				
								Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		
								JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴		
								Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge						
								JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²						
								Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge						
JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴														

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 50mm x Dia: 2.46mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 50mm x Root Dia: 3.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 100mm x Root Dia: 4.00mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 100mm x Root Dia: 4.00mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Structural Laminated Veneer Lumber – Mixed Wood Species: Radiata Pine & Larch – Plies: ≥ 24 – Thickness: 45mm - Width: 300mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	300x45 LVL 10 F11	General Structural Use	F11	A	Phenolic Formaldehyde Resin	-	E ₀	12949	65.5	6.0	10.5	-	10747	60.0	5.0	7.9	-	33.9	38.0	19/03/2026

Structural Laminated Veneer Lumber – Mixed Wood Species: Radiata Pine & Larch – Plies: ≥ 38 – Thickness: 63mm - Width: 95mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	95x63 LVL 12 F11/F14	General Structural Use	F11 F14	A	Phenolic Formaldehyde Resin	-	E ₀	12372	56.91	4.2	9.0	-	12564	60.9	3.6	4.7	-	24.7	30.2	19/03/2026

Structural Laminated Veneer Lumber – Mixed Wood Species: Radiata Pine & Larch – Plies: ≥ 28 – Thickness: 45mm - Width: 240mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f'_b [MPa]	On Edge f'_s [MPa]	On Edge f'_p [MPa]	On Edge f'_{sj} [MPa]	On Flat E [MPa]	On Flat f'_b [MPa]	On Flat f'_s [MPa]	On Flat f'_p [MPa]	On Flat f'_{sj} [MPa]	Axial f'_t [MPa]	Axial f'_c [MPa]	Date Endorsed
FINWOOD	240x45 LVL 12 F11/F14	General Structural Use	F11 F14	A	Phenolic Formaldehyde Resin	-	E ₀	12305	55.0	-	-	-	12942	53.3	-	-	-	-	-	19/03/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>

Structural Laminated Veneer Lumber – Mixed Wood Species: Radiata Pine & Larch – Plies: ≥ 33 – Thickness: 63mm - Width: 65mm																					
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f'_b [MPa]	On Edge f'_s [MPa]	On Edge f'_p [MPa]	On Edge f'_{sj} [MPa]	On Flat E [MPa]	On Flat f'_b [MPa]	On Flat f'_s [MPa]	On Flat f'_p [MPa]	On Flat f'_{sj} [MPa]	Axial f'_t [MPa]	Axial f'_c [MPa]	Date Endorsed	
FINWOOD	65x63 LVL 11 E11	General Structural Use	E11	A	Phenolic Formaldehyde Resin	-	Super E ₀	11835	59.6	5.4	14.4	-	13004	63.7	3.9	7.9	-	28.3	31.7	19/03/2026	
						Nails				Screws				Bolts							
						Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face		Lateral Parallel Face		Lateral Perpendicular Face		Lateral Parallel Face					
						JD5 ⁵		JD5 ⁶		JD5 ⁹		JD5 ¹⁰		JD5 ¹³		JD5 ¹⁴					
						Lateral Parallel Edge		Lateral Perpendicular Edge		Lateral Parallel Edge		Lateral Perpendicular Edge									
						JD5 ⁷		JD5 ⁸		JD5 ¹¹		JD5 ¹²									
						Withdrawal Face		Withdrawal Edge		Withdrawal Face		Withdrawal Edge									
JD5 ¹		JD5 ²		JD5 ³		JD5 ⁴															

1. Withdrawal Loads for Nails Driven into Face-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
2. Withdrawal Loads for Nails Driven into Edge-Nail (Bullet Head Nails 90mm x Dia: 3.67mm)
3. Withdrawal Loads for Screws Driven into Face-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
4. Withdrawal Loads for Screws Driven into Edge-Screw (Self-Drilling Screws 90mm x Root Dia: 4.00mm)
5. Lateral Loaded Parallel to Grain, Driven into Face-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)
6. Lateral Loaded Perpendicular to Grain, Driven into Face-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)
7. Lateral Loaded Parallel to Grain, Driven into Edge-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)

8. Lateral Loaded Perpendicular to Grain, Driven into Edge-Nail (Bullet Head Nails 120mm x Dia: 5.00mm)
9. Lateral Loaded Parallel to Grain, Driven into Face-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
10. Lateral Loaded Perpendicular to Grain, Driven into Face-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
11. Lateral Loaded Parallel to Grain, Driven into Edge-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
12. Lateral Loaded Perpendicular to Grain, Driven into Edge-Screw (Self-Drilling Screws 120mm x Root Dia: 5.00mm)
13. Lateral Loaded Parallel to Grain, Driven into Face-Bolt (M12 x 150mm)
14. Lateral Loaded Perpendicular to Grain, Driven into Face-Bolt (M12 x 150mm)

Structural Laminated Veneer Lumber – Mixed Wood Species: Spruce & Radiata Pine – Plies: ≥ 23 – Thickness: 45mm - Width: 63mm																				
Brand	Model	Use	Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge f_b' [MPa]	On Edge f_s' [MPa]	On Edge f_p' [MPa]	On Edge f_{sj}' [MPa]	On Flat E [MPa]	On Flat f_b' [MPa]	On Flat f_s' [MPa]	On Flat f_p' [MPa]	On Flat f_{sj}' [MPa]	Axial f_t' [MPa]	Axial f_c' [MPa]	Date Endorsed
FINWOOD	63x45 LVL 12 F14	General Structural Use	F14	A	Phenolic Formaldehyde Resin	-	Super E ₀	13164	63.5	5.7	12.4	-	13894	58.8	4.5	7.8	-	26.5	29.6	28/04/2026

End of Record

Certificate No: PC10291

Originally Certified: 01/09/2026

Updated: 01/09/2026

Expires: 01/09/2031

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>

