



# Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Fuzhou Lexfit Plastic Co., Ltd.  
Chikeng Industrial Zone, Longtian Town  
Fuqing City, Fujian Province, 350311, China  
W: [www.xlpvcpipefittings.com](http://www.xlpvcpipefittings.com)  
T: +86 18617380184

**Subject to the following conditions and limitations:**

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI Certification (CMI), and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland  
CMI Certification Pty Ltd  
PO Box 273, Palmwoods, Qld 4555, Australia  
ABN: 81 663 250 815  
T: + 61 7 5445 2199  
W: [www.cmicert.com.au](http://www.cmicert.com.au)  
E: [office@cmicert.com.au](mailto:office@cmicert.com.au)



080070	09/11/2023	09/11/2023	09/11/2028	AS/NZS 1477:2017 PVC pipes and fittings for pressure applications (Including Best Environmental Practice PVC compliance)
CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website [www.abcb.gov.au](http://www.abcb.gov.au)





# Schedule To

## Fuzhou Lexfit Plastic Co., Ltd.



### APPLICABLE STANDARD/SPECIFICATION

AS/NZS 1477:2017 PVC pipes and fittings for pressure applications  
(Including Best Environmental Practice PVC compliance)

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
LEXFIT/ER PVC	PVC Pressure Pipe	800.15.PN15	PVC Pressure Pipe DN15 PN15 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.20.PN15	PVC Pressure Pipe DN20 PN15 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.25.PN15	PVC Pressure Pipe DN25 PN15 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.32.PN12	PVC Pressure Pipe DN32 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023

LEXFIT/ER PVC	PVC Pressure Pipe	800.40.PN12	PVC Pressure Pipe DN40 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.50.PN12	PVC Pressure Pipe DN50 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.65.PN12	PVC Pressure Pipe DN65 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.80.PN12	PVC Pressure Pipe DN80 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.100.PN12	PVC Pressure Pipe DN100 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023
LEXFIT/ER PVC	PVC Pressure Pipe	800.150.PN12	PVC Pressure Pipe DN150 PN12 S1 White or Grey	For Water Supply, Drain, Waste and Vent Use Only Suitable for Indoor and Outdoor Use Max Temp Continuous 30°C Max temp Intermediate: 60°C<100 hrs within 49yrs Operating Pressure: 10bar Max Velocity: 0.7m/s	N/A	09/11/2023

\*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

**End of Record**