

Ashbury Oak



100
CABLE OAK



110
ROTTNEST OAK



170
BREAMLEA OAK



180
MORETON OAK



300
NORFOLK OAK



500
COTTESLOE OAK



510
SHELLY OAK



520
AIRLIE OAK



540
FAIRHAVEN OAK



720
BELLARINE OAK



730
WHITSUNDAY OAK



790
SEAFORD OAK

Ashbury Oak

Ashbury Oak allows you to bring a stunning natural timber look to your floor, with the benefits of hybrid. With no need to seal, installation is quick and easy. You'll be able to walk on your new floor the very same day. Choose from a stunning selection of natural timber styles that will add instant appeal in to any space.

Technical Data

Type:	Hybrid Flooring	Finish:	Matte
Dimensions:	1830mm x 182mm	Surface:	Embossed in Register
Thickness:	6.5mm	Top Layer:	Decorative Film & Wear Layer
Wear Layer:	0.5mm	Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Units Per Box:	4 boards	Backing Layer:	1.5mm Acoustic Backing
m² per box:	1.332	Profile:	Micro Bevel
m² per pallet:	113.24	Coating System:	Ceramic Bead
Colours:	12	Installation Method:	Uniclic®
Country of Origin:	China		

Performance

Dimensional Stability:	(ISO 23999) Length: 0.0, Width: 0.0, Curling: 0.0	Flammability:	(EN ISO 9239) CRF 11.1kW/m2
Abrasion Rating:	(EN 660-2) Group T	Smoke Value:	(EN ISO 9239) 210% minutes
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet	Slip Resistance:	(AS 4586) P4
Light Fastness:	(EN ISO 105-B02) ≥6	Warranty:	25 Year Hybrid Limited Residential Warranty*
Light Reflectance Values:	100 - 55.8 110 - 43.5 170 - 12.3 180 - 8.1 300 - 18.2 500 - 33.6 510 - 27.6 520 - 24.9 540 - 26.5 720 - 30.2 730 - 13.1 790 - 15.3		

Sustainability

Product Transparency:	Global Green Tag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits

