

# Metropol 1200



**180**  
**Mountain**  
**Hardwood**



**305**  
**Natural Hardwood**




**350**  
**Golden Oak**



**505**  
**Southern Oak**




**510**  
**Sand Oak**



**535**  
**Northern**  
**Weathered Gum**



**540**  
**Summer Blackbutt**



**559**  
**Southern**  
**Weathered Gum**



**570**  
**High Country**  
**Hardwood**



**710**  
**Coastal Hardwood**



**730**  
**Sun Bleached**  
**Hardwood**



**750**  
**Hidden Valley**

# Metropol 1200

A durable floor with exquisite design, Metropol 1200 is a technologically advanced hybrid range that ticks all the right boxes. Available in a wide range of natural timber hues, you can enhance any space with a strong, stable and beautiful flooring that's easy to install.

## Technical Data

<b>Type:</b>	Hybrid Flooring	<b>Finish:</b>	Matte
<b>Dimensions:</b>	1200mm x 182mm	<b>Surface:</b>	Embossed
<b>Total Product Thickness:</b>	6mm	<b>Top Layer:</b>	Decorative Film & Wear Layer
<b>Wear Layer:</b>	0.3mm	<b>Substrate Layer:</b>	Trigon® Core Technology (Limestone Composite)
<b>Units Per Box:</b>	10 boards	<b>Backing Layer:</b>	1.5mm Acoustic Backing
<b>m² per box:</b>	2.184	<b>Profile:</b>	Micro Bevel
<b>m² per pallet:</b>	120.12	<b>Coating System:</b>	PUR
<b>Colours:</b>	12	<b>Installation Method:</b>	Uniclic®

## Performance

<b>Dimensional Stability:</b>	(ISO 23999) Length: 0.0, Width: 0.05, Curling: 0.0	<b>Flammability:</b>	(EN ISO 9239) CRF 11.0kW/m2
<b>Abrasion Rating:</b>	(EN 660-2) Group P	<b>Smoke Value:</b>	(EN ISO 9239) 121% minutes
<b>Impact Sound Reduction:</b>	Please refer to Godfrey Hirst Acoustic Performance specification sheet	<b>Slip Resistance:</b>	(AS 4586) P3
<b>Light Fastness:</b>	(EN ISO 105-B02) ≥6	<b>Warranty:</b>	25 Year Hybrid Limited Residential Warranty*
<b>Light Reflectance Values:</b>	180 - 9.30   305 - 20.51   350 - 10.81   505 - 16.33   510 - 36.78   535 - 15.19   540 - 24.11   559 - 9.73   570 - 19.39   710 - 28.83   730 - 24.20   750 - 18.52		

## Sustainability

<b>Product Transparency:</b>	Global Green Tag, GreenRate Level A certified
<b>Accreditation:</b>	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
<b>Indoor Air Quality:</b>	Green Building Council Compliant for VOC emission rate limits

