



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Guangdong Liansu Technology Industrial Co., Ltd.

Liansu Industrial Estate, Longjiang Town,
Shunde Zone, Foshan, Guangdong 528318, China

W: www.lesso.com

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland

CMI Certification Pty Ltd

PO Box 273, Palmwoods, Qld 4555, Australia

ABN: 81 663 250 815

T: + 61 7 5445 2199

W: www.cmcert.com.au

E: office@cmcert.com.au



080111	13/11/2025	13/11/2025	13/11/2030	AS/NZS 1260:2017 PVC-U pipes and fitting for drain, waste and vent applications
--------	------------	------------	------------	---

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
-----------------------	-------------------------------	-------------------------------	------------------------------	--------------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Guangdong Liansu Technology Industrial Co., Ltd.

APPLICABLE
STANDARD/SPECIFICATION



AS/NZS 1260:2017 PVC-U pipes and fitting for drain, waste and vent applications

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
LESSO	Plain Wall Fitting	IT50	DWV PVC COMBO INSPECTION TEE - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IT65	DWV PVC COMBO INSPECTION TEE - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IT100	DWV PVC COMBO INSPECTION TEE - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IT150	DWV PVC COMBO INSPECTION TEE - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	SC50	DWV STRAIGHTCOUPLINGS F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	SC65	DWV STRAIGHTCOUPLINGS F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	SC100	DWV STRAIGHTCOUPLINGS F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	SC150	DWV STRAIGHTCOUPLINGS F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IJ50	DWV I.O. PLAIN JUNCTION F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IJ65	DWV I.O. PLAIN JUNCTION F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025

LESSO	Plain Wall Fitting	IJ100	DWV I.O. PLAIN JUNCTION F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IJ150	DWV I.O. PLAIN JUNCTION F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCC50	DWV PAN CONNECTOR(CONCENTRIC) - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCC65	DWV PAN CONNECTOR(CONCENTRIC) - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCC100	DWV PAN CONNECTOR(CONCENTRIC) - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCC150	DWV PAN CONNECTOR(CONCENTRIC) - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCO50	DWV PAN CONNECTOR(OFFSET) - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCO65	DWV PAN CONNECTOR(OFFSET) - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCO100	DWV PAN CONNECTOR(OFFSET) - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PCO150	DWV PAN CONNECTOR(OFFSET) - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	CAP50	DWV CAP PUSH ON - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	CAP65	DWV CAP PUSH ON - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	CAP100	DWV CAP PUSH ON - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	CAP150	DWV CAP PUSH ON - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025

LESSO	Plain Wall Fitting	FWG50	DWV PVC FLOOR WASTE GULLY - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	FWG65	DWV PVC FLOOR WASTE GULLY - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	FWG100	DWV PVC FLOOR WASTE GULLY - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	FWG150	DWV PVC FLOOR WASTE GULLY - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45B50	DWV 45°BEND F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45B65	DWV 45°BEND F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45B100	DWV 45°BEND F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45B150	DWV 45°BEND F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BPE50	DWV 88° BEND PLAIN END F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BPE65	DWV 88° BEND PLAIN END F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BPE100	DWV 88° BEND PLAIN END F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BPE150	DWV 88° BEND PLAIN END F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88IB50	DWV 88° I.O. BEND F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88IB65	DWV 88° I.O. BEND F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88IB100	DWV 88° I.O. BEND F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025

LESSO	Plain Wall Fitting	88IB150	DWV 88° I.O. BEND F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45PJ50	DWV 45° PLAIN JUNCTION F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45PJ65	DWV 45° PLAIN JUNCTION F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45PJ100	DWV 45° PLAIN JUNCTION F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	45PJ150	DWV 45° PLAIN JUNCTION F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PJ50	DWV PLAIN JUNCTION F&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PJ65	DWV PLAIN JUNCTION F&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PJ100	DWV PLAIN JUNCTION F&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	PJ150	DWV PLAIN JUNCTION F&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IC50	DWV INSPECTION CAP - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IC65	DWV INSPECTION CAP - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IC100	DWV INSPECTION CAP - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	IC150	DWV INSPECTION CAP - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIS50	DWV 88° BEND IN SOCKET M&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIS65	DWV 88° BEND IN SOCKET M&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025

LESSO	Plain Wall Fitting	88BIS100	DWV 88° BEND IN SOCKET M&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIS150	DWV 88° BEND IN SOCKET M&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIP50	DWV 88° BEND IN PIPE M&F - DN50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIP65	DWV 88° BEND IN PIPE M&F - DN65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIP100	DWV 88° BEND IN PIPE M&F - DN100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	88BIP150	DWV 88° BEND IN PIPE M&F - DN150	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	RE6550	DWV PIPE REDUCER F&F - DN65 x 50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	RE10050	DWV PIPE REDUCER F&F - DN100 x 50	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	RE10065	DWV PIPE REDUCER F&F - DN100 x 65	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Fitting	RE150100	DWV PIPE REDUCER F&F - DN150 x 100	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Pipe	PIPE50	PVC-U Drain Straight Pipe - DN50 x 2.2mm	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Pipe	PIPE65	PVC-U Drain Straight Pipe - DN65 x 2.7mm	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Pipe	PIPE100	PVC-U Drain Straight Pipe - DN100 x 3.0mm – SN6	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025
LESSO	Plain Wall Pipe	PIPE150	PVC-U Drain Straight Pipe - DN150 x 4.0mm – SN4	Suitable for above or below ground Long-term max service Temp: 45°C Short-term max service Temp: 60°C	N/A	13/11/2025

*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record