

## **Certificate of Conformity**

THIS CERTIFICATE IS GRANTED TO

### Heshan Gute Hardware Sanitary Ware Industry Co., Ltd

Dongxi Industry Zone, Zhishan Town, Heshan City, Guangdong Province, 529729 China

#### Subject to the following conditions and limitations:

- 1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
- 2 The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
- Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder
- 4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Certificate number: WM080099-I01-R01

Talissa Ireland **CMI Certification Pty Ltd**PO Box 273, Palmwoods, Qld 4555, Australia

ABN: 81 663 250 815

T: + 61 7 5445 2199

W: <a href="https://cmicert.com.au">https://cmicert.com.au</a></a>
E: <a href="mailto:office@cmicert.com.au">office@cmicert.com.au</a>



080099 19/08/2025 14/10/2025 19/08/2030 AS 3718:2021 Water supply - tap ware

CERTIFICATE INITIAL CURRENT CERTIFICATION APPLICABLE
NUMBER CERTIFICATION DATE CERTIFICATION DATE EXPIRY DATE STANDARD/SPECIFICATION

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au







## **Schedule To**

# Heshan Gute Hardware Sanitary Ware Industry Co., Ltd



APPLICABLE STANDARD/SPECIFICATION

AS 3718:2021 Water supply - tap ware

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
GUTE	Basin Mixer	GTM-001	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-002	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-003	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-004	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-005	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-006	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-007	Basin Mixer – Stainless Steel SUS304 – 25mm outlet in front Ceramic Cartridge – Flow Controller PERLATOR HC COINSLOT STD PCA 1.75gpm 45.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-008	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE HC TJ PCA 1.75gpm 43.2261.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025

Certificate number: WM080099-I01-R01 This certificate may only be reproduced in its entirety. Page 2 of 7

GUTE	Basin Mixer	GTM-009	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE HC TJ PCA 1.75gpm 43.2261.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Basin Mixer	GTM-010	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-011	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Shower Mixer	GTL-A001	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A002	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A003	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A004	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A005	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A006	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A007	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A008	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A009	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-A010	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Torque Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Basin Spout	GTM-A001	Basin Spout – Stainless Steel SUS304 – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A002	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C	Υ	19/08/2025

Certificate number: WM080099-I01-R01 This certificate may only be reproduced in its entirety. Page 3 of 7

				Pressure: 50 to 750kPa		
GUTE	Basin Mixer	GTM-A003	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A004	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A005	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A006	Basin Mixer – Stainless Steel SUS304 – Quick Turn Ceramic Cartridge G 1/2 – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Spout	GTM-A007	Basin Spout – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A008	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A009	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE HC TJ PCA 1.75gpm 43.2261.010 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A010	Basin Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE HC TJ PCA 1.75gpm 43.2261.010 WMKA21177	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Basin Mixer	GTM-A013	Basin Mixer – Stainless Steel SUS304 – Quick Turn Ceramic Cartridge G 1/2 – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer	GTC-001	Kitchen Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer	GTC-002	Kitchen Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer	GTC-003	Kitchen Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-004	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Flow Controller PCW ½ 8.0L/min 58.8638.1 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling — Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025

GUTE	Kitchen Mixer - Pull out	GTC-005	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer - Pull down	GTC-006	Kitchen Mixer - Pull down – Stainless Steel SUS304 – 25mm Low Torque Ceramic Cartridge – Flow Controller PERLATOR HC COINSLOT STD PCA 1.75gpm 45.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer -Pull out	GTC-007	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-008	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-009	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC COINSLOT STD PCA 1.75gpm 45.2061.000  WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8  Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-010	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC COINSLOT STD PCA 1.75gpm 45.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer	GTC-011	Kitchen Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer -Pull down	GTC-012	Kitchen Mixer - Pull down – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-013	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-014	Kitchen Mixer - Pull out — Stainless Steel SUS304 — 35mm Flat Seat Ceramic Cartridge with plastic housing — Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 — Flow Controller PCW 1/ 8.0L/min 58.8638.1 WMKA21177 - Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling — Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025

Certificate number: WM080099-I01-R01

This certificate may only be reproduced in its entirety. Page 5 of 7

GUTE	Kitchen Mixer - Pull out	GTC-015	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Kitchen Mixer - Pull out	GTC-016	Kitchen Mixer - Pull out – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller CACHE Honeycomb TT PCA 5.0L 44.3251.010 WMKA21177 – Flow Controller PCW 1/8.0L/min 58.8638.1 WMKA21177 - Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1 - Stainless Steel & PEX Flexible Hose DN 6 Braided Quick Coupling M8*1 - Stainless Steel & PEX Flexible Hose DN 8 Nylon Braided G1/2 Quick Coupling – Check Valve	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Kitchen Mixer	GTC-017	Kitchen Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller FLOW THRU STD IT D.5 6 PCA 6.0L/min 02.5112.1 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Kitchen Mixer	GTC-018	Kitchen Mixer – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Filter Tap	GTC-J001	Filter Tap – Stainless Steel SUS304 – Ceramic Cartridge G1/2 Quick Turn	Temp: 2°C to 80°C Pressure; 50 to 750kPa	Υ	19/08/2025
GUTE	Filter Tap	GTC-J002	Filter Tap – Stainless Steel SUS304 – 35mm Flat Seat Ceramic Cartridge with plastic housing – Stainless Steel & PEX Flexible Hose DN 6 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Filter Tap	GTC-J003	Filter Tap – Stainless Steel SUS304 – Ceramic Cartridge G1/2 Quick Turn	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	19/08/2025
GUTE	Angle Valve	GTP-J001	Angle Valve – Staínless Steel SUS304 – Ceramic Cartridge G1/2 Quick Turn	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Angle Valve	GTP-J002	Angle Valve – Stainless Steel SUS304 – Ceramic Cartridge G1/2 Quick Turn	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Angle Valve	GTP-J003	Angle Valve – Stainless Steel SUS304 – Ceramic Cartridge G1/2 Quick Turn	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Y	19/08/2025
GUTE	Shower Set	GTL-M001	Shower Set – Stainless Steel SUS304 – 35mm High Pressure Low Torque Ceramic Cartridge – Flow Controller PCW ½ 9.0L/min 58.8639.1 WMKA21177 – Spring Hose & PU G1/2 G1/2 DN8	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Mixer	GTL-M002	Shower Mixer – Stainless Steel SUS304 – 35mm High Pressure Low Torque Ceramic Cartridge	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Shower Set	GTL-M003	Shower Set – Stainless Steel SUS304 – 35mm High Pressure Low Torque Ceramic Cartridge – Flow Controller PCW ½ 9.0L/min 58.8639.1 WMKA21177 – Spring Hose & PU G1/2 G1/2 DN8	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025

Certificate number: WM080099-I01-R01

This certificate may only be reproduced in its entirety. Page 6 of 7

GUTE	Floor Standing Bath Filler with Hand Shower	GTL-L001	Floor Standing Bath Filler with Hand Shower – Stainless Steel SUS304 – 35mm High Pressure Low Torque Ceramic Cartridge – Flow Controller PCW ½ 9.0L/min 58.8639.1 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 8 Braided G1/2 M10*1 - Spring Hose & PU G1/2 G1/2 DN8	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Floor Standing Bath Filler with Hand Shower	GTL-L002	Floor Standing Bath Filler with Hand Shower – Stainless Steel SUS304 – 35mm High Pressure Low Torque Ceramic Cartridge – Flow Controller PCW ½ 9.0L/min 58.8639.1 WMKA21177 – Stainless Steel & PEX Flexible Hose DN 8 Braided G1/2 M10*1 - Spring Hose & PU G1/2 G1/2 DN8	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Bath Mixer	GTL-L003	Bath Mixer – Stainless Steel SUS304 – 35mm High Pressure Low Torque Ceramic Cartridge – Flow Controller PERLATOR HC STD PCA 1.75gpm 40.2061.000 WMKA21177 - Stainless Steel & PEX Flexible Hose DN 8 Braided G1/2 M10*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	N/A	19/08/2025
GUTE	Basin Faucet	GTM-012	Basin Faucet - Stainless Steel SUS304 – 35mm combined cartridge with distributor – Flow Controller Nerperl 40.2052.000 WMKA21177 - Stainless Steel & PEX Flexible Hose DN 8 Braided G1/2 M8*1	Temp: 2°C to 80°C Pressure: 50 to 750kPa	Υ	14/10/2025

<sup>\*</sup>Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

