



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Howest Pty Ltd

299A Canterbury Road, Revesby, NSW 2212, Australia

ABN 68 065 886 740

T 02 9792 2255

E sales@howest.com.au

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland

CMI Certification Pty Ltd

PO Box 273, Palmwoods, Qld 4555, Australia

ABN: 81 663 250 815

T: + 61 7 5445 2199

W: <https://cmicert.com.au>

E: office@cmicert.com.au



080118	02/02/2026	02/02/2026	02/02/2031	AS 3718:2021 Water supply – Tap ware
--------	------------	------------	------------	--------------------------------------

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JASANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Howest Pty Ltd

APPLICABLE
STANDARD/SPECIFICATION



AS 3718:2021 Water supply – Tap ware

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
EASYHOME	Kitchen Mixer Tap	HH-2510	Kitchen Faucet with GAO0706* Stainless Steel Flexible Hose SUS304 + PEX + Brass DN6 F1/2*M8x1, PEX inner tube, 10CM-200CM WM074914 - C19-7L Flow Controller WM074669 - K25PN 25mm flat feet Cartridge WM074671	Working Pressure: min 150kPa - max 500kPa. Working Temperature: min 2°C - max 60°C (kitchen application), min 2°C - max 50°C (All other areas).	Yes	02/02/2026
EASYHOME	Kitchen Mixer Tap	HH-2512	Kitchen Faucet with GAO0706* Stainless Steel Flexible Hose SUS304 + PEX + Brass, DN6 F1/2*M8x1, PEX inner tube 10CM-200CM WM074914 - C19-5L Flow Controller WM074669 - K35P-03NPX 35mm flat feet Cartridge WM074671	Working Pressure: min 150kPa - max 500kPa. Working Temperature: min 2°C - max 60°C (kitchen application), min 2°C - max 50°C (All other areas).	Yes	02/02/2026

*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record