



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Jiangmen Good Will Co.,Ltd

4th Floor, Building 3 (Workshop), No. 23 Yexing 1st Road,
Huicheng, Xinhui District, Jiangmen, Guangdong 529100 China

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
 2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
 3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
1. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland
CMI Certification Pty Ltd
PO Box 273, Palmwoods, Qld 4555, Australia
ABN: 81 663 250 815
T: + 61 7 5445 2199
W: www.cmicert.com.au
E: office@cmicert.com.au



080130	23/04/2026	23/04/2026	23/04/2031	AS 3718:2021 Water supply – tap ware
--------	------------	------------	------------	--------------------------------------

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Jiangmen Good Will Co.,Ltd



APPLICABLE
STANDARD/SPECIFICATION

AS 3718:2021 Water supply – tap ware

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
JGW	Basin Mixer	B1007 01	Basin Mixer - CW511L - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823 - 45.2061.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLOT STD PCA 1.75gpm, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1007 02	Basin Mixer - CW511L - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823 - 45.2061.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLOT STD PCA 1.75gpm, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1007 27	Basin Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823 - 45.2061.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLOT STD PCA 1.75gpm, WMKA21177	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1010 01-1	Basin Mixer - SUS304 - 35D-10 & Ceramic Cartridge, 35mm low torque cartridge with distributor, WMKA21823 - 44.3251.010 & CACHÉ HC TT PCA, CACHÉ Honeycomb TT PCA 5.0L, WMKA21177 - XL- WM8-03 & Flexible Water Connectors, Stainless Steel braided hose, Length 150mm to 2000mm Class 4 WM-032267	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1010 01	Basin Mixer - SUS304 - 35D-10 & Ceramic Cartridge, 35mm low torque cartridge with distributor, WMKA21823 - 44.3251.010 & CACHÉ HC TT PCA, CACHÉ Honeycomb TT PCA 5.0L, WMKA21177 - XL-WM8-03 & Flexible Water Connectors, Stainless Steel braided hose, Length 150mm to 2000mm Class 4 WM-032267	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1010 02	Basin Mixer - SUS304 - 35D-10 & Ceramic Cartridge, 35mm low torque cartridge with distributor, WMKA21823 - 44.3251.010 & CACHÉ HC TT PCA, CACHÉ Honeycomb TT PCA 5.0L, WMKA21177 – XL-WM8-03 & Flexible Water Connectors, Stainless Steel braided hose, Length 150mm to 2000mm Class 4 WM-032267	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026

JGW	Basin Mixer	B1028 01	Basin Mixer - SUS304 - 35D-10 & Ceramic Cartridge, 35mm low torque cartridge with distributor, WMKA21823 - 44.3251.010 & CACHÉ HC TT PCA, CACHÉ Honeycomb TT PCA 5.0L, WMKA21177 – XL-WM8-03 & Flexible Water Connectors, Stainless Steel braided hose, Length 150mm to 2000mm Class 4 WM-032267	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1028 02	Basin Mixer - SUS304 - 35D-10 & Ceramic Cartridge, 35mm low torque cartridge with distributor, WMKA21823 - 44.3251.010 & CACHÉ HC TT PCA, CACHÉ Honeycomb TT PCA 5.0L, WMKA21177 - XL-WM8-03 & Flexible Water Connectors, Stainless Steel braided hose, Length 150mm to 2000mm Class 4 WM-032267	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1010 28	Basin Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823 - 45.2061.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLOT STD PCA 1.75gpm, WMKA21177	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1016 01	Basin Mixer - SUS304 - 35H-1 & Ceramic Cartridge, 35mm High Seat Ceramic Cartridge, plastic housing, WMKA21823 - 40.2252.010 & CACHÉ HC STD PCA, CACHÉ HC STD PCA 6.0L/min, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1016 02	Basin Mixer - SUS304 - 35H-1 & Ceramic Cartridge, 35mm High Seat Ceramic Cartridge, plastic housing, WMKA21823 - 40.2252.010 & CACHÉ HC STD PCA, CACHÉ HC STD PCA 6.0L/min, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1016 28	Basin Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823 - 45.2061.220 & PERLATOR HC CS JR PCA, PERLATOR HC CS JR M 13/16-27 PCA 1.75 gpm, WMKA21177	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1018 01	Basin Mixer - CW511L - W25D & Ceramic Cartridge, 25mm low torque cartridge, WMKA21823 - 45.2061.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLOT STD PCA 1.75gpm, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1018 02	Basin Mixer - CW511L - W25D & Ceramic Cartridge, 25mm low torque cartridge, WMKA21823 - 45.2061.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLOT STD PCA 1.75gpm, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B1018 28	Basin Mixer - Ceramic Cartridge, plastic housing, WMKA21823 - 45.2061.220 & PERLATOR HC CS JR PCA, PERLATOR HC CS JR M 13/16-27 PCA 1.75 gpm, WMKA21177	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026

JGW	Basin Mixer	B029 01	Basin Mixer - SUS304 - W25H & Ceramic Cartridge, 25mm high torque cartridge, WMKA21823 - 45.2061.220 & PERLATOR HC CS JR PCA, PERLATOR HC CS JR M 13/16-27 PCA 1.75 gpm, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B029 02	Basin Mixer - SUS304 - W25H & Ceramic Cartridge, 25mm high torque cartridge, WMKA21823 - 45.2061.220 & PERLATOR HC CS JR PCA, PERLATOR HC CS JR M 13/16-27 PCA 1.75 gpm, WMKA21177 - SOFTPEX DN6 with Stainless Steel braiding - LD, LF or SS, WMKA21165	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Basin Mixer	B029 27	Basin Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823 - 45.2056.000 & PERLATOR HC CS PCA, PERLATOR HC COINSLT STD PCA 1.5gpm, WMKA21177	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026
JGW	Concealed Mixer	SO1007 21	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1007 22	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1010B 21	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1010B 22	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1016 21	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1016 22	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1018 21	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO1018 22	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO029 21	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Concealed Mixer	SO029 22	Concealed Mixer - SUS304 - 35D-1 & Ceramic Cartridge, 35mm Flat Seat Ceramic Cartridge, plastic housing, WMKA21823	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	N/A	23/04/2026
JGW	Kitchen Mixer	K132 03	Kitchen Mixer - SUS304 - 35D-10 & Ceramic Cartridge, 35mm low torque cartridge with distributor, WMKA21823 - 40.2052.000 & PERLATOR HC STD PCA, PERLATOR HC STD PCA 6.0L, WMKA21177 - XL-WM8-03 & Flexible Water Connectors, Stainless Steel braided hose, Length 150mm to 2000mm Class 4 WM-032267	Working Pressure: 0.05Mpa to 1Mpa Working Temperature: 0°C to 55°C	Yes	23/04/2026

*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record