

Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Jina Enterprises Ptv Ltd T/A Enflair

74-76 Lee Holm Road. St Marys, NSW 2760, Australia ABN: 33 644 556 258

W: https://enflair.com.au/ E: info@enflair.com.au

Subject to the following conditions and limitations:

- 1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
- 2 The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
- 3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder
- 1. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under. and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland **CMI Certification Pty Ltd** PO Box 273. Palmwoods. Qld 4555. Australia

T: +61 7 5445 2199 W: www.cmicert.com.au E: office@cmicert.com.au

ABN: 81 663 250 815



080082 03/11/2023 03/11/2023 02/11/2028 AS 3718:2021 Water supply – Tap ware

CERTIFICATE INITIAL CERTIFICATION APPLICABLE **CURRENT** NUMBER CERTIFICATION DATE **CERTIFICATION DATE EXPIRY DATE** STANDARD/SPECIFICATION

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au







Schedule To

Jina Enterprises Pty Ltd T/A Enflair



APPLICABLE
STANDARD/SPECIFICATION
AS 3718:2021 Water supply – Tap ware

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed		
Enflair	Basin Mixer	K1113-31	Tall Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1113-10	Tall Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1113-20	Tall Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1113-32	Tall Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1113-33	Tall Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1111-31	Short Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1111-10	Short Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1111-20	Short Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		
Enflair	Basin Mixer	K1111-32	Short Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023		

Enflair	Basin Mixer	K1111-33	Short Basin Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 1.75gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Basin Mixer	K1132-31	Concealed Basin Faucet & Mixer – Stainless Steel SUS304 – Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Basin Mixer	K1132-10	Concealed Basin Faucet & Mixer – Stainless Steel SUS304 – Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Basin Mixer	K1132-20	Concealed Basin Faucet & Mixer – Stainless Steel SUS304 – Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Basin Mixer	K1132-32	Concealed Basin Faucet & Mixer – Stainless Steel SUS304 – Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Basin Mixer	K1132-33	Concealed Basin Faucet & Mixer – Stainless Steel SUS304 – Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-31-0-110	Bathtub Spout - Stainless Steel SUS304 - Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-10-0-110	Bathtub Spout - Stainless Steel SUS304 - Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-20-0-110	Bathtub Spout - Stainless Steel SUS304 - Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-32-0-110	Bathtub Spout - Stainless Steel SUS304 - PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-33-0-110	Bathtub Spout - Stainless Steel SUS304 - PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-31-0-150	Bathtub Spout - Stainless Steel SUS304 - Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-10-0-150	Bathtub Spout - Stainless Steel SUS304 - Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-20-0-150	Bathtub Spout - Stainless Steel SUS304 - Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-32-0-150	Bathtub Spout - Stainless Steel SUS304 – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-33-0-150	Bathtub Spout - Stainless Steel SUS304 – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-31-0-180	Bathtub Spout - Stainless Steel SUS304 - Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-10- <mark>0-180</mark>	Bathtub Spout - Stainless Steel SUS304 - Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-20-0-180	Bathtub Spout - Stainless Steel SUS304 - Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-32-0-180	Bathtub Spout - Stainless Steel SUS304 – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-33-0-180	Bathtub Spout - Stainless Steel SUS304 – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-31-0-220	Bathtub Spout - Stainless Steel SUS304 – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-10-0-220	Bathtub Spout - Stainless Steel SUS304 - Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-20-0-220	Bathtub Spout - Stainless Steel SUS304 – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202

Enflair	Bathtub Spout	K1150-32-0-220	Bathtub Spout - Stainless Steel SUS304 – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Bathtub Spout	K1150-33-0-220	Bathtub Spout - Stainless Steel SUS304 – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Kitchen Mixer	K1621-31	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Kitchen Mixer	K1621-10	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Kitchen Mixer	K1621-20	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS304 - with Flexible Braided Stainless Steel \$S304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/202
Enflair	Kitchen Mixer	K1621-32	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1621-33	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1120-31	Kitchen Faucet & Mixer – Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1120-10	Kitchen Faucet & Mixer – Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1120-20	Kitchen Faucet & Mixer – Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1120-32	Kitchen Faucet & Mixer – Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1120-33	Kitchen Faucet & Mixer – Stainless Steel SUS304 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1 – Aerator Flow Controller 5.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1121-31	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1121-10	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20
Enflair	Kitchen Mixer	K1121-20	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/20

F . 0 - 1 -	Kishaa Waas	1//4/04 20	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2	Working Pressure: 0.05mpa to 1mpa	NIA	02/44/0002
Enflair	Kitchen Mixer	K1121-32	M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Kitchen Mixer	K1121-33	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Kitchen Mixer	K1821-31	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Kitchen Mixer	K1821-10	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel \$S304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Kitchen Mixer	K1821-20	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Kitchen Mixer	K1821-32	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Kitchen Mixer	K1821-33	Pull-Out Kitchen Faucet & Mixer – Pull Out - Stainless Steel SUS316 - with Flexible Braided Stainless Steel SS304 & PEX Hose DN8 G1/2 M10*1– Aerator Flow Controller 1.2gpm – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1130-31	Shower Mixer - Stainless Steel SUS304 - 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1130-10	Shower Mixer - Stainless Steel SUS304 - 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1130-20	Shower Mixer - Stainless Steel SUS304 - 35mm Flat Seat Ceramic & Plastic Cartridge Controller –Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1130-32	Shower Mixer - Stainless Steel SUS304 - 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1130-33	Shower Mixer - Stainless Steel SUS304 - 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1131-31	Shower Mixer - Stainless Steel SUS304 - 40mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1131-10	Shower Mixer - Stainless Steel SUS304 - 40mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1131-20	Shower Mixer - Stainless Steel SUS304 - 40mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1131-32	Shower Mixer - Stainless Steel SUS304 - 40mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Shower Mixer	K1131-33	Shower Mixer - Stainless Steel SUS304 - 40mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Bathtub Mixer	K1143-31	Free Standing Bathtub Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 Shower Hose EPDM DN14 G1/2 G 1/2– Aerator Flow Controller 9.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Brushed	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023

Enflair	Bathtub Mixer	K1143-10	Free Standing Bathtub Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 Shower Hose EPDM DN14 G1/2 G 1/2– Aerator Flow Controller 9.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Bathtub Mixer	K1143-20	Free Standing Bathtub Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 Shower Hose EPDM DN14 G1/2 G 1/2– Aerator Flow Controller 9.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – Chrome Matte Black	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Bathtub Mixer	K1143-32	Free Standing Bathtub Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 Shower Hose EPDM DN14 G1/2 G 1/2– Aerator Flow Controller 9.0L/min – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Brushed Gold	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023
Enflair	Bathtub Mixer	K1143-33	Free Standing Bathtub Faucet & Mixer – Stainless Steel SUS304 – with Flexible Braided Stainless Steel SS304 Shower Hose EPDM DN14 G1/2 G 1/2– Aerator Flow Controller 9.0Lmin – 35mm Flat Seat Ceramic & Plastic Cartridge Controller – PVD Gun Grey	Working Pressure: 0.05mpa to 1mpa Working Temperature: 0°C to 55°C	N/A	03/11/2023

^{*}Lead Free compliance in accordance with NCC 2022 - Volume Three - Plumbing Code of Australia - A5G4(2)(b)

