



# Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

**Kaiping Dongsheng Sanitary Ware Industrial Co., Ltd**

No. 247-249, Xinshi North Road, Shikou Town,  
Kaiping City, Guangdong 529321 China

**Subject to the following conditions and limitations:**

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland  
**CMI Certification Pty Ltd**  
PO Box 273, Palmwoods, Qld 4555, Australia  
ABN: 81 663 250 815  
T: + 61 7 5445 2199  
W: [www.cmcert.com.au](http://www.cmcert.com.au)  
E: [office@cmcert.com.au](mailto:office@cmcert.com.au)



080076	12/09/2023	01/05/2026	30/04/2028	AS 3718:2021 Water supply - Tapware
--------	------------	------------	------------	-------------------------------------

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website [www.abcb.gov.au](http://www.abcb.gov.au)





# Schedule To

Kaiping Dongsheng Sanitary Ware Industrial Co., Ltd



APPLICABLE  
STANDARD/SPECIFICATION  
AS3718:2021 Water supply - Tapware

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
CUICHENG/fienza®	Basin Mixer	101182	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Distributor Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101110	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Distributor Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	2668	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	213.109	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	2669	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	213.107	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	2629	Basin Mixer with Spout – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Distributor Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	211.103	Basin Mixer with Spout – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Distributor Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023

CUICHENG/fienza®	Basin Mixer	5001	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	5002	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	5005	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	217.103	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	5006	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	217.107	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101135	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101136	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101988B	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101888B	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Maximum Working Pressure: 1.0Mpa Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101192	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	101193	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	101194	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	225.109	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	101195	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	225.107	Basin Mixer with Spout – DR Brass – 35mm Ceramic Mixer Cartridge - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	109122	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023

CUICHENG	Basin Mixer	111048	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	225.103	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	111049	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	217.106	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Basin Mixer	5045	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Basin Mixer	217.105	Basin Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Shower Mixer with Shower Head	109125	Shower Mixer with Shower Head – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 9.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Shower Mixer with Shower Head	217.102	Shower Mixer with Shower Head – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 9.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Shower Mixer with Shower Head	111035	Shower Mixer with Shower Head – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 9.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Shower Mixer with Shower Head	217.101	Shower Mixer with Shower Head – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flow Controller 9.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Concealed Shower Mixer	NT85	Concealed Shower Mixer – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Concealed Shower Mixer	225.101	Concealed Shower Mixer – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Concealed Shower/Bath Mixer with Diverter	111034	Concealed Shower/Bath Mixer with Diverter – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Concealed Shower/Bath Mixer with Diverter	225.102	Concealed Shower/Bath Mixer with Diverter – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Concealed Shower Mixer	NT86	Concealed Shower Mixer – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Concealed Shower Mixer	211.101	Concealed Shower Mixer – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Concealed Shower/Bath Mixer with Diverter	NT87	Concealed Shower/Bath Mixer with Diverter – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Concealed Shower/Bath Mixer with Diverter	211.102	Concealed Shower Mixer – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Concealed Shower Mixer	5123	Concealed Shower Mixer – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
fienza®	Concealed Shower Mixer	213.101	Concealed Shower Mixer – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Concealed Shower/Bath Mixer with Diverter	109103	Concealed Shower/Bath Mixer with Diverter – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023

fienza®	Concealed Shower/Bath Mixer with Diverter	213.102	Concealed Shower/Bath Mixer with Diverter – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	N/A	12/09/2023
CUICHENG	Kitchen Mixer	2630	Kitchen Mixer with Spout – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Kitchen Mixer	211.105	Kitchen Mixer with Spout – DR Brass – 40mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Kitchen Mixer	3313C	Kitchen Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Kitchen Mixer	213.111	Kitchen Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Kitchen Mixer	104062	Kitchen Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG	Kitchen Mixer	104133	Kitchen Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
fienza®	Kitchen Mixer	225.105	Kitchen Mixer with Spout – DR Brass – 35mm Single Lever Ceramic Mixer Cartridge with Standard Base & Plastic Housing - Flexible Hose SUS304/SUS316 DN8 G1/2xM10*1 PEX Inner Tube – Flow Controller 7.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 4°C to 90°C	No**	12/09/2023
CUICHENG/fienza®	Basin Mixer	DS8104	Basin Mixer – DR Lead Free Brass – 26mm Ceramic Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	DS8105	Basin Mixer – DR Lead Free Brass – 26mm Ceramic Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	DS8106	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	DS8107	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	DS8108	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 5.0L/min	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	M3311	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	M3312	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	M3301	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	M3302	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	M3303	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Basin Mixer	M3304	Basin Mixer – DR Lead Free Brass – 35mm Mixer Cartridge – Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 1.5gpm	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025



CUICHENG/fienza®	Shower Mixer	M3350	Shower Mixer – DR Brass - 40mm Ceramic Mixer Cartridge – Shower Hose DN14 G1/2 G1/2 EPDM Hose - Flow Controller 2.5gpm x 2	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Shower Mixer - Wall Concealed Faucet Main Body	DS906	Shower Mixer - Wall Concealed Faucet Main Body - DR Brass - 35mm Mixer Cartridge	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Shower Mixer - Wall Concealed Faucet Main Body	DS907	Shower Mixer - Wall Concealed Faucet Main Body - DR Brass - 35mm Mixer Cartridge	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Shower Mixer - Wall Concealed Faucet Main Body	DS908	Shower Mixer - Wall Concealed Faucet Main Body - DR Brass - 35mm Mixer Cartridge	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Shower Mixer - Wall Concealed Faucet Main Body	DS909	Shower Mixer - Wall Concealed Faucet Main Body - DR Brass - 35mm Mixer Cartridge	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Shower Mixer	M3351	Shower Mixer – 40mm Ceramic Mixer Cartridge – DR Brass - Shower Hose DN14 G1/2 G1/2 EPDM Hose - Flow Controller 2.5gpm x 2	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Standing-Floor Bathtub/Shower Mixer	M3343	Standing-Floor Bathtub/Shower Mixer - DR Brass - 35mm Mixer Cartridge - Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 2.5gpm - Shower Hose DN14 G1/2 G1/2 EPDM Hose	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Standing-Floor Bathtub/Shower Mixer	M3345	Standing-Floor Bathtub/Shower Mixer - DR Brass - 35mm Mixer Cartridge - Flexible Hose SUS304 DN 8 G1/2 M10*1 PEX Inner Tube - Flow Controller 2.5gpm - Shower Hose DN14 G1/2 G1/2 EPDM Hose	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	N/A	14/02/2025
CUICHENG/fienza®	Tap Angle Valve	DS701	Tap Angle Valve - DR Lead Free Brass	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025
CUICHENG/fienza®	Tap Angle Valve	DS702	Tap Angle Valve - DR Lead Free Brass	Working Pressure: 0.5 - 1.0Mpa Working Temperature: 1°C to 65°C	Yes	14/02/2025

\*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

\*\* Product is not Lead Free compliant

**End of Record**