



# Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

## KAIPING LOY PLUMBING CO., LTD

Workshop 701, Building 2, No. 58, Jinshan East Avenue, Shuikou Town,  
Kaiping City, Guangdong, China

### Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
  2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
  3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
1. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland  
**CMI Certification Pty Ltd**  
PO Box 273, Palmwoods, Qld 4555, Australia  
ABN: 81 663 250 815  
T: + 61 7 5445 2199  
W: [www.cmicert.com.au](http://www.cmicert.com.au)  
E: [office@cmicert.com.au](mailto:office@cmicert.com.au)



080114	29/05/2026	29/05/2026	29/05/2031	AS 3718:2021 Water supply – tap ware
--------	------------	------------	------------	--------------------------------------

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website [www.abcb.gov.au](http://www.abcb.gov.au)





# Schedule To

## KAIPING LOY PLUMBING CO., LTD

APPLICABLE  
STANDARD/SPECIFICATION  
AS 3718:2021 Water supply – tap ware



Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No*/Not Applicable	Date Endorsed
Watersense	Bidet Sprayer	S01	Shattaf Set - Stainless Steel Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P01	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P02	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P03	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P21	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P20	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	B03	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	B04	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	B07	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	B08	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	B09	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026



Watersense	Bidet Faucet	BW10-1	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Faucet	BW03-1	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Faucet	BW03-2	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Faucet	BW01-1	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker- DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Faucet	BW01-2	Shattaf Set - Brass Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P10	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P11	Shattaf Set - Plastic Sprayer, Brass Valve body - Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026
Watersense	Bidet Sprayer	P15	Shattaf Set - Plastic Sprayer, Brass Valve body -Atmospheric vacuum breaker - DN 6 braid hose, G1/2, G1/2	Maximum Working Pressure: 0.5Mpa Recommended Working Pressure: 0.1-0.5Mpa Recommended Hot Water Temperature: 65°C	N/A	29/05/2026

\*Lead Free compliance in accordance with NCC 2025 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

**End of Record**