



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Kaiping Thun Sanitary Ware Co.,Ltd

No.48 Jiaxing South Road, Shuikou Town,
Kaiping City, Guangdong, 529321, China

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland
CMI Certification Pty Ltd
PO Box 273, Palmwoods, Qld 4555, Australia
ABN: 81 663 250 815
T: + 61 7 5445 2199
W: <https://cmicert.com.au>
E: office@cmicert.com.au



080109	28/05/2026	28/05/2026	28/05/2031	AS/NZS 3662:2005 Performance of showers for bathing
--------	------------	------------	------------	---

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JASANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Kaiping Thun Sanitary Ware Co.,Ltd

APPLICABLE
STANDARD/SPECIFICATION
AS/NZS 3662:2005 Performance of showers for bathing



Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
THUN	Shower Head	LJ-S702A	Shower Head, DN15 G1/2, Flow controller WMKA21177-58.8639.1	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Head	LJ-S703A	Shower Head, DN15 G1/2, Flow controller WMKA21177-58.8639.1	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S601	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4158.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S601A	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4158.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Head	LJ-S710	Shower head, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S622	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4159.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S611	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4159.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Head	LJ-S702B	Shower head, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Head	LJ-S702C	Shower head, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Head	LJ-S703B	Shower head, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Head	LJ-S703C	Shower head, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Hose	LJ-S901	Shower Hose, DN15 G1/2	Working pressure: 0~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026

THUN	Shower Hose	LJ-S902	Shower Hose, DN15 G1/2	Working pressure: 0~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S623	Hand Shower, DN15 G1/2B, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S631	Hand Shower, DN15 G1/2B, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S635	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4159.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S633	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4159.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Hand Shower	LJ-S637	Hand Shower, DN15 G1/2, Flow controller WMKA21177-31.4159.0	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S810 (Set1)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S810 (Set2)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S811 (Set1)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S811 (Set2)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S811 (Set3)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S811 (Set5)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S812 (Set1)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S812 (Set2)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S812 (Set3)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S812 (Set5)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S820 (Set1)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S820 (Set2)	Single Lever Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S821 (Set1)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026

THUN	Shower Set	LJ-S821 (Set2)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S822 (Set1)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S822 (Set2)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L for both showerhead and hand shower, S901 shower hose	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S312 (Set1)	Multi-Function Hand Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S312 (Set2)	Multi-Function Hand Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S312 (Set3)	Multi-Function Hand Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S313 (Set1)	Multi-Function Hand Shower, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S800 (Set1)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S800 (Set2)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026
THUN	Shower Set	LJ-S802 (Set1)	Rail Shower Set, DN15 G1/2, Flow controller WM 74669-C19-9L	Working pressure: 0.15~0.5MPa Working temperature: 0~55°C	N/A	28/05/2026

*Lead Free compliance in accordance with NCC 2025 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record