



CMI ProdCert
PC10287

CERTIFICATE OF CONFORMITY

This is to certify that

Linyi Wenwei Trading Co., Ltd.

Is certified to manufacture products to:

AS 6669:2016 Plywood – Formwork
AS/NZS 2269.0:2012 Plywood - Structural Specifications

Certificate Holder

Linyi Wenwei Trading Co., Ltd.
Zhoujingpu Village, Yitang Town,
Lanshan District, Linyi, Shandong
276000 China

W: www.wenweiwood.com

Certification Body



CMI Certification Pty Ltd

ABN: 81 663 250 815

JASANZ Accreditation No. Z4450210AK

PO Box 273, Palmwoods Qld 4555,
Australia

Ph: +61 7 5445 2199

E: office@cmicert.com.au

W: <https://cmicert.com.au/>

Product Description

Structural Plywood and Formwork Plywood

Product Purpose or Use

Structural Plywood and Formwork Plywood

Subject to the following Conditions & Limitations:

Nil

Certificate No: PC10287

Originally Certified: 03/09/2026

Updated: 03/09/2026

Expires: 03/09/2031

Talissa Ireland

CMI Certification Pty Ltd



- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>





CMI ProdCert
PC10287

CERTIFICATE OF CONFORMITY

This is to certify that

Linyi Wenwei Trading Co., Ltd.

Is certified to manufacture products to:

AS 6669:2016 Plywood – Formwork

Brand	Model	Description	Date Endorsed
Wenwei	F27 Formply 17mm	17mm Formply Plywood – Eucalyptus – 13ply – CC, A Bond, Super E ₀ , Class 2 17 (I 200.7 – Z 22.9 / I 221.0 – Z 26.4) Parallel: E 20044 MPa; f'_b 95.6 MPa; f'_s 9.5 MPa; Perpendicular: E 18805 MPa; f'_b 76.8 MPa; f'_s 8.4 MPa	03/09/2026
Wenwei	F22 Formply 17mm	17mm Formply Plywood – Eucalyptus – 13ply – CC, A Bond, Super E ₀ , Class 2 17 (I 200.7 – Z 22.9 / I 221.0 – Z 26.4) Parallel: E 20044 MPa; f'_b 95.6 MPa; f'_s 9.5 MPa; Perpendicular: E 18805 MPa; f'_b 76.8 MPa; f'_s 8.4 MPa	03/09/2026
Wenwei	F17 Formply 17mm	17mm Formply Plywood – Eucalyptus – 13ply – CC, A Bond, Super E ₀ , Class 2 17 (I 200.7 – Z 22.9 / I 221.0 – Z 26.4) Parallel: E 20044 MPa; f'_b 95.6 MPa; f'_s 9.5 MPa; Perpendicular: E 18805 MPa; f'_b 76.8 MPa; f'_s 8.4 MPa	03/09/2026
Wenwei	F17 HEXA Formply 17mm	17mm Formply Plywood – Eucalyptus – 13ply – CC, A Bond, Super E ₀ , Class 2 17 (I 200.7 – Z 22.9 / I 221.0 – Z 26.4) Parallel: E 20044 MPa; f'_b 95.6 MPa; f'_s 9.5 MPa; Perpendicular: E 18805 MPa; f'_b 76.8 MPa; f'_s 8.4 MPa	03/09/2026
Wenwei	F17 WIREMESH Formply 17mm	17mm Formply Plywood – Eucalyptus – 13ply – CC, A Bond, Super E ₀ , Class 2 17 (I 200.7 – Z 22.9 / I 221.0 – Z 26.4) Parallel: E 20044 MPa; f'_b 95.6 MPa; f'_s 9.5 MPa; Perpendicular: E 18805 MPa; f'_b 76.8 MPa; f'_s 8.4 MPa	03/09/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Wenwei	F17 Formply 17mm	17mm Formply Plywood – Eucalyptus & Walnut – 11ply – CC, A Bond, Super E ₀ , Class 2 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 14089 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; Perpendicular: E 15598 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa	03/09/2026
Wenwei	F17 HEXA Formply 17mm	17mm Formply Plywood – Eucalyptus & Walnut – 11ply – CC, A Bond, Super E ₀ , Class 2 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 14089 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; Perpendicular: E 15598 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa	03/09/2026
Wenwei	F17 WIREMESH Formply 17mm	17mm Formply Plywood – Eucalyptus & Walnut – 11ply – CC, A Bond, Super E ₀ , Class 2 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 14089 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; Perpendicular: E 15598 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa	03/09/2026
Wenwei	F14 Formply 17mm	17mm Formply Plywood – Eucalyptus & Walnut – 11ply – CC, A Bond, Super E ₀ , Class 2 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 12000 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; Perpendicular: E 12000 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa	03/09/2026

AS/NZS 2269.0:2012 Plywood - Structural Specifications

Brand	Model	Description	Date Endorsed
Wenwei	F14 Ply 12mm	12mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 12 (I 73.9 – Z 11.9 / I 74.5 – Z 14.0) Parallel: E 13088 MPa; f'_b 66.4 MPa; f'_s 5.9 MPa; f'_t 32.8 MPa; f'_c 32.6 MPa Perpendicular: E 14188 MPa; f'_b 59.8 MPa; f'_s 5.8 MPa; f'_t 32.8 MPa; f'_c 36.5 MPa	03/09/2026
Wenwei	F11 Ply 12mm	12mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 12 (I 73.9 – Z 11.9 / I 74.5 – Z 14.0) Parallel: E 10500 MPa; f'_b 66.4 MPa; f'_s 5.9 MPa; f'_t 32.8 MPa; f'_c 32.6 MPa Perpendicular: E 10500 MPa; f'_b 59.8 MPa; f'_s 5.8 MPa; f'_t 32.8 MPa; f'_c 36.5 MPa	03/09/2026
Wenwei	F8 Ply 12mm	12mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 12 (I 73.9 – Z 11.9 / I 74.5 – Z 14.0) Parallel: E 9100 MPa; f'_b 66.4 MPa; f'_s 5.9 MPa; f'_t 32.8 MPa; f'_c 32.6 MPa Perpendicular: E 9100 MPa; f'_b 59.8 MPa; f'_s 5.8 MPa; f'_t 32.8 MPa; f'_c 36.5 MPa	03/09/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmcert.com.au/>

Wenwei	F17 Ply 17mm	17mm Structural Plywood – Walnut & Eucalyptus – 11ply – CC, A Bond, Super E ₀ , 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 14089 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; f'_t 52.2 MPa; f'_c 39.8 MPa Perpendicular: E 15598 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa; f'_t 57.8 MPa; f'_c 43.2 MPa	03/09/2026
Wenwei	F14 Ply 17mm	17mm Structural Plywood – Walnut & Eucalyptus – 11ply – CC, A Bond, Super E ₀ , 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 12000 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; f'_t 52.2 MPa; f'_c 39.8 MPa Perpendicular: E 12000 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa; f'_t 57.8 MPa; f'_c 43.2 MPa	03/09/2026
Wenwei	F11 Ply 17mm	17mm Structural Plywood – Walnut & Eucalyptus – 11ply – CC, A Bond, Super E ₀ , 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 10500 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; f'_t 52.2 MPa; f'_c 39.8 MPa Perpendicular: E 10500 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa; f'_t 57.8 MPa; f'_c 43.2 MPa	03/09/2026
Wenwei	F8 Ply 17mm	17mm Structural Plywood – Walnut & Eucalyptus – 11ply – CC, A Bond, Super E ₀ , 17 (I 214.4 – Z 24.5 / I 207.3 – Z 25.4) Parallel: E 9100 MPa; f'_b 60.4 MPa; f'_s 7.4 MPa; f'_t 52.2 MPa; f'_c 39.8 MPa Perpendicular: E 9100 MPa; f'_b 52.4 MPa; f'_s 7.6 MPa; f'_t 57.8 MPa; f'_c 43.2 MPa	03/09/2026
Wenwei	F17 Ply 7mm	7mm Structural Plywood – Radiata Pine & Eucalyptus – 5ply – CD, A Bond, Super E ₀ , 7 (I 14.4 – Z 4.0 / I 15.1 – Z 5.1) Parallel: E 14021 MPa; f'_b 62.1 MPa; f'_s 7.5 MPa; f'_t 28.7 MPa; f'_c 37.2 MPa Perpendicular: E 14158 MPa; f'_b 54.8 MPa; f'_s 6.6 MPa; f'_t 27.7 MPa; f'_c 36.5 MPa	03/09/2026
Wenwei	F14 Ply 7mm	7mm Structural Plywood – Radiata Pine & Eucalyptus – 5ply – CD, A Bond, Super E ₀ , 7 (I 14.4 – Z 4.0 / I 15.1 – Z 5.1) Parallel: E 12000 MPa; f'_b 62.1 MPa; f'_s 7.5 MPa; f'_t 28.7 MPa; f'_c 37.2 MPa Perpendicular: E 12000 MPa; f'_b 54.8 MPa; f'_s 6.6 MPa; f'_t 27.7 MPa; f'_c 36.5 MPa	03/09/2026
Wenwei	F11 Ply 7mm	7mm Structural Plywood – Radiata Pine & Eucalyptus – 5ply – CD, A Bond, Super E ₀ , 7 (I 14.4 – Z 4.0 / I 15.1 – Z 5.1) Parallel: E 10500 MPa; f'_b 62.1 MPa; f'_s 7.5 MPa; f'_t 28.7 MPa; f'_c 37.2 MPa Perpendicular: E 10500 MPa; f'_b 54.8 MPa; f'_s 6.6 MPa; f'_t 27.7 MPa; f'_c 36.5 MPa	03/09/2026
Wenwei	F8 Ply 7mm	7mm Structural Plywood – Radiata Pine & Eucalyptus – 5ply – CD, A Bond, Super E ₀ , 7 (I 14.4 – Z 4.0 / I 15.1 – Z 5.1) Parallel: E 9100 MPa; f'_b 62.1 MPa; f'_s 7.5 MPa; f'_t 28.7 MPa; f'_c 37.2 MPa Perpendicular: E 9100 MPa; f'_b 54.8 MPa; f'_s 6.6 MPa; f'_t 27.7 MPa; f'_c 36.5 MPa	03/09/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmcert.com.au/>

Wenwei	F17 Ply 9mm	9mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 9 (I 31.5 – Z 6.8 / I 31.1 – Z 7.7) Parallel: E 14560 MPa; f'_b 61.2 MPa; f'_s 6.1 MPa; f'_t 30.1 MPa; f'_c 36.8 MPa Perpendicular: E 14286 MPa; f'_b 46.3 MPa; f'_s 5.8 MPa; f'_t 29.5 MPa; f'_c 37.6 MPa	03/09/2026
Wenwei	F14 Ply 9mm	9mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 9 (I 31.5 – Z 6.8 / I 31.1 – Z 7.7) Parallel: E 12000 MPa; f'_b 61.2 MPa; f'_s 6.1 MPa; f'_t 30.1 MPa; f'_c 36.8 MPa Perpendicular: E 12000 MPa; f'_b 46.3 MPa; f'_s 5.8 MPa; f'_t 29.5 MPa; f'_c 37.6 MPa	03/09/2026
Wenwei	F11 Ply 9mm	9mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 9 (I 31.5 – Z 6.8 / I 31.1 – Z 7.7) Parallel: E 10500 MPa; f'_b 61.2 MPa; f'_s 6.1 MPa; f'_t 30.1 MPa; f'_c 36.8 MPa Perpendicular: E 10500 MPa; f'_b 46.3 MPa; f'_s 5.8 MPa; f'_t 29.5 MPa; f'_c 37.6 MPa	03/09/2026
Wenwei	F8 Ply 9mm	9mm Structural Plywood – Radiata Pine & Eucalyptus – 7ply – CD, A Bond, Super E ₀ , 9 (I 31.5 – Z 6.8 / I 31.1 – Z 7.7) Parallel: E 9100 MPa; f'_b 61.2 MPa; f'_s 6.1 MPa; f'_t 30.1 MPa; f'_c 36.8 MPa Perpendicular: E 9100 MPa; f'_b 46.3 MPa; f'_s 5.8 MPa; f'_t 29.5 MPa; f'_c 37.6 MPa	03/09/2026
Wenwei	F17 Ply 15mm	15mm Structural Plywood – Radiata Pine & Eucalyptus – 9ply – CC, A Bond, Super E ₀ , 15 (I 149.9 – Z 19.4 / I 139.8 – Z 19.6) Parallel: E 14558 MPa; f'_b 65.4 MPa; f'_s 7.2 MPa; f'_t 31.7 MPa; f'_c 36.4 MPa Perpendicular: E 14010 MPa; f'_b 54.3 MPa; f'_s 6.8 MPa; f'_t 31.9 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F14 Ply 15mm	15mm Structural Plywood – Radiata Pine & Eucalyptus – 9ply – CC, A Bond, Super E ₀ , 15 (I 149.9 – Z 19.4 / I 139.8 – Z 19.6) Parallel: E 12000 MPa; f'_b 65.4 MPa; f'_s 7.2 MPa; f'_t 31.7 MPa; f'_c 36.4 MPa Perpendicular: E 12000 MPa; f'_b 54.3 MPa; f'_s 6.8 MPa; f'_t 31.9 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F11 Ply 15mm	15mm Structural Plywood – Radiata Pine & Eucalyptus – 9ply – CC, A Bond, Super E ₀ , 15 (I 149.9 – Z 19.4 / I 139.8 – Z 19.6) Parallel: E 10500 MPa; f'_b 65.4 MPa; f'_s 7.2 MPa; f'_t 31.7 MPa; f'_c 36.4 MPa Perpendicular: E 10500 MPa; f'_b 54.3 MPa; f'_s 6.8 MPa; f'_t 31.9 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F8 Ply 15mm	15mm Structural Plywood – Radiata Pine & Eucalyptus – 9ply – CC, A Bond, Super E ₀ , 15 (I 149.9 – Z 19.4 / I 139.8 – Z 19.6) Parallel: E 9100 MPa; f'_b 65.4 MPa; f'_s 7.2 MPa; f'_t 31.7 MPa; f'_c 36.4 MPa Perpendicular: E 9100 MPa; f'_b 54.3 MPa; f'_s 6.8 MPa; f'_t 31.9 MPa; f'_c 37.7 MPa	03/09/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmcert.com.au/>

Wenwei	F17 Ply 19mm	19mm Structural Plywood – Radiata Pine & Eucalyptus – 11ply – CD, A Bond, Super E ₀ , 19 (I 298.4 – Z 30.5 / I 290.4 – Z 31.6) Parallel: E 15260 MPa; f'_b 65.0 MPa; f'_s 5.7 MPa; f'_t 40.1 MPa; f'_c 40.3 MPa Perpendicular: E 14188 MPa; f'_b 46.0 MPa; f'_s 5.2 MPa; f'_t 39.1 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F14 Ply 19mm	19mm Structural Plywood – Radiata Pine & Eucalyptus – 11ply – CD, A Bond, Super E ₀ , 19 (I 298.4 – Z 30.5 / I 290.4 – Z 31.6) Parallel: E 12000 MPa; f'_b 65.0 MPa; f'_s 5.7 MPa; f'_t 40.1 MPa; f'_c 40.3 MPa Perpendicular: E 12000 MPa; f'_b 46.0 MPa; f'_s 5.2 MPa; f'_t 39.1 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F11 Ply 19mm	19mm Structural Plywood – Radiata Pine & Eucalyptus – 11ply – CD, A Bond, Super E ₀ , 19 (I 298.4 – Z 30.5 / I 290.4 – Z 31.6) Parallel: E 10500 MPa; f'_b 65.0 MPa; f'_s 5.7 MPa; f'_t 40.1 MPa; f'_c 40.3 MPa Perpendicular: E 10500 MPa; f'_b 46.0 MPa; f'_s 5.2 MPa; f'_t 39.1 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F8 Ply 19mm	19mm Structural Plywood – Radiata Pine & Eucalyptus – 11ply – CD, A Bond, Super E ₀ , 19 (I 298.4 – Z 30.5 / I 290.4 – Z 31.6) Parallel: E 9100 MPa; f'_b 65.0 MPa; f'_s 5.7 MPa; f'_t 40.1 MPa; f'_c 40.3 MPa Perpendicular: E 9100 MPa; f'_b 46.0 MPa; f'_s 5.2 MPa; f'_t 39.1 MPa; f'_c 37.7 MPa	03/09/2026
Wenwei	F17 Ply 21mm	21mm Structural Plywood – Radiata Pine & Eucalyptus – 13ply – CD, A Bond, Super E ₀ , 21 (I 400.7 – Z 37.1 / I 394.2 – Z 38.6) Parallel: E 14056 MPa; f'_b 66.3 MPa; f'_s 5.1 MPa; f'_t 36.5 MPa; f'_c 39.9 MPa Perpendicular: E 14043 MPa; f'_b 46.1 MPa; f'_s 5.3 MPa; f'_t 35.3 MPa; f'_c 37.8 MPa	03/09/2026
Wenwei	F14 Ply 21mm	21mm Structural Plywood – Radiata Pine & Eucalyptus – 13ply – CD, A Bond, Super E ₀ , 21 (I 400.7 – Z 37.1 / I 394.2 – Z 38.6) Parallel: E 12000 MPa; f'_b 66.3 MPa; f'_s 5.1 MPa; f'_t 36.5 MPa; f'_c 39.9 MPa Perpendicular: E 12000 MPa; f'_b 46.1 MPa; f'_s 5.3 MPa; f'_t 35.3 MPa; f'_c 37.8 MPa	03/09/2026
Wenwei	F11 Ply 21mm	21mm Structural Plywood – Radiata Pine & Eucalyptus – 13ply – CD, A Bond, Super E ₀ , 21 (I 400.7 – Z 37.1 / I 394.2 – Z 38.6) Parallel: E 10500 MPa; f'_b 66.3 MPa; f'_s 5.1 MPa; f'_t 36.5 MPa; f'_c 39.9 MPa Perpendicular: E 10500 MPa; f'_b 46.1 MPa; f'_s 5.3 MPa; f'_t 35.3 MPa; f'_c 37.8 MPa	03/09/2026
Wenwei	F8 Ply 21mm	21mm Structural Plywood – Radiata Pine & Eucalyptus – 13ply – CD, A Bond, Super E ₀ , 21 (I 400.7 – Z 37.1 / I 394.2 – Z 38.6) Parallel: E 9100 MPa; f'_b 66.3 MPa; f'_s 5.1 MPa; f'_t 36.5 MPa; f'_c 39.9 MPa Perpendicular: E 9100 MPa; f'_b 46.1 MPa; f'_s 5.3 MPa; f'_t 35.3 MPa; f'_c 37.8 MPa	03/09/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>

Wenwei	F17 Ply 25mm	25mm Structural Plywood – Radiata Pine & Eucalyptus – 15ply – CD, A Bond, Super E ₀ , 25 (I 681.4 – Z 53.0 / I 659.7 – Z 53.8) Parallel: E 15018 MPa; f'_b 48.0 MPa; f'_s 5.7 MPa; f'_t 34.2 MPa; f'_c 38.8 MPa Perpendicular: E 14594 MPa; f'_b 51.6 MPa; f'_s 5.7 MPa; f'_t 38.2 MPa; f'_c 37.8 MPa	03/09/2026
Wenwei	F14 Ply 25mm	25mm Structural Plywood – Radiata Pine & Eucalyptus – 15ply – CD, A Bond, Super E ₀ , 25 (I 681.4 – Z 53.0 / I 659.7 – Z 53.8) Parallel: E 12000 MPa; f'_b 48.0 MPa; f'_s 5.7 MPa; f'_t 34.2 MPa; f'_c 38.8 MPa Perpendicular: E 12000 MPa; f'_b 51.6 MPa; f'_s 5.7 MPa; f'_t 38.2 MPa; f'_c 37.8 MPa	03/09/2026
Wenwei	F11 Ply 25mm	25mm Structural Plywood – Radiata Pine & Eucalyptus – 15ply – CD, A Bond, Super E ₀ , 25 (I 681.4 – Z 53.0 / I 659.7 – Z 53.8) Parallel: E 10500 MPa; f'_b 48.0 MPa; f'_s 5.7 MPa; f'_t 34.2 MPa; f'_c 38.8 MPa Perpendicular: E 10500 MPa; f'_b 51.6 MPa; f'_s 5.7 MPa; f'_t 38.2 MPa; f'_c 37.8 MPa	03/09/2026
Wenwei	F8 Ply 25mm	25mm Structural Plywood – Radiata Pine & Eucalyptus – 15ply – CD, A Bond, Super E ₀ , 25 (I 681.4 – Z 53.0 / I 659.7 – Z 53.8) Parallel: E 9100 MPa; f'_b 48.0 MPa; f'_s 5.7 MPa; f'_t 34.2 MPa; f'_c 38.8 MPa Perpendicular: E 9100 MPa; f'_b 51.6 MPa; f'_s 5.7 MPa; f'_t 38.2 MPa; f'_c 37.8 MPa	03/09/2026

End of Record

Certificate No: PC10287

Originally Certified: 03/09/2026

Updated: 03/09/2026

Expires: 03/09/2031

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>