

# CERTIFICATE OF CONFORMITY

This is to certify that

## Nordin Industries Australia Pty Ltd

Is certified to manufacture products to:

**AS/NZS 4357.0:2022 Structural laminated veneer lumber, Part 0: Specifications**



CMI ProdCert  
**PC10237**

### Certificate Holder

**Nordin Industries Australia Pty Ltd**  
27 Atkinson Rd, Taren Point, NSW 2229  
Australia  
ABN: 44 685 595 859  
Ph: +61 2 9588 4422  
E: [info@nordins.com.au](mailto:info@nordins.com.au)  
W: <https://nordins.com.au/>

### Certification Body



**CMI Certification Pty Ltd**  
ABN: 81 663 250 815  
JAS-ANZ Accreditation No.  
Z4450210AK  
PO Box 273, Palmwoods Qld 4555,  
Australia  
Ph: +61 7 5445 2199  
E: [office@cmicert.com.au](mailto:office@cmicert.com.au)  
W: <https://cmicert.com.au/>

### Product Description

Structural Laminated Veneer Lumber

### Product Purpose or Use

Structural Laminated Veneer Lumber

### Subject to the following Conditions & Limitations:

Nil

**Certificate No:** PC10237

**Originally Certified:** 26/03/2026

**Updated:** 26/03/2026

**Expires:** 26/03/2031

**Talissa Ireland**  
CMI Certification Pty Ltd



- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>





# CERTIFICATE OF CONFORMITY

This is to certify that

## Nordin Industries Australia Pty Ltd

Is certified to manufacture products to:

### AS/NZS 4357.0:2022 Structural laminated veneer lumber, Part 0: Specifications

Wood Species: Mixed Species Radiata Pine & Larch – Plies: ≥ 27 – Thickness: ≥ 45mm – Width: ≥ 95mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_p$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_p$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	95 x 45 LVL F17	General Structural Use	F17 (Flat Only)	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	12530	59	4.8	7.0	-	14371	64	4.4	3.7	-	40.2	36.8	26/03/2026

Wood Species: Spruce – Plies: ≥ 15 – Thickness: ≥ 65mm – Width: ≥ 95mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_p$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_p$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	95 x 65 LVL F17	General Beams Used on Edge Only	F17	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	14000	54.5	4.5	10.1	-	-	-	-	-	-	-	-	26/03/2026

Wood Species: Spruce – Plies: ≥ 15 – Thickness: ≥ 63mm – Width: ≥ 95mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_p$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_p$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	95 x 63 LVL E14 F17	General Beams Used on Edge Only	F17	A	-	-	E <sub>0</sub>	14000	54.5	4.5	10.1	-	-	-	-	-	-	-	-	26/03/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Wood Species: Spruce – Plies: ≥ 23 – Thickness: ≥ 75mm – Width: ≥ 150mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	150 x 75 LVL F14	General Beams Used on Edge Only	F14	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	13200	61	4.4	9.6	-	-	-	-	-	-	-	-	26/03/2026

Wood Species: Spruce – Plies: ≥ 18 – Thickness: ≥ 35mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	90 x 35 LVL E12 F14	General Structural Use	F14	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	12014	55.0	4.0	8.7	-	12046	54.7	4.4	4.0	-	32.7	34.0	26/03/2026

Wood Species: Spruce – Plies: ≥ 23 – Thickness: ≥ 45mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	90 x 45 LVL E12 F14	General Structural Use	F14	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	12808	60.9	4.1	7.7	-	13323	59.8	4.3	4.1	-	31.2	31.5	26/03/2026

Wood Species: Larch – Plies: ≥ 18 – Thickness: ≥ 35mm – Width: ≥ 70/90/120/140/150/170/190mm																					
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	Width	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	70/90/120/140/150/170/190 x 35 LVL E16 F22	General Structural Use	F22	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	70	16194	78.1	7.4	10.9	16211	74.2	6.5	8.7	-	43.4	48.6	26/03/2026	
								120	16172	65.2	5.4	10.9									
								190	17025	70.8	5.5	10.9									

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



**Wood Species: Larch – Plies: ≥ 23 – Thickness: ≥ 45mm – Width: ≥ 90/120/140/150/170/190/200/240/290/300mm**

Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	Width	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed	
NordinPine	90/120 /140/1 50/170 /190/2 00/240 /290/3 00 x 45 LVL E14 F17	General Structural Use	F17	A	Phenolic Formaldehyde Resin	-	E <sub>0</sub>	90	15109	72.7	5.3	10.9	14741	67.8	5.3	8.7	-	35.8	41.8	26/03/2026
								190	14384	72	5.2	10.9								
								290	15553	68.7	5.2	10.9								

**Wood Species: Spruce – Plies: ≥ 23 – Thickness: ≥ 77mm – Width: ≥ 150mm**

Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed	
NordinPine	150 x 77 LVL F14	General Beams Used on Edge Only	F14	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	13200	61	4.4	9.6	-	-	-	-	-	-	-	-	26/03/2026

**Wood Species: Spruce – Plies: ≥ 18 – Thickness: ≥ 35mm – Width: ≥ 90mm**

Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed	
NordinPine	E10 F8	General Beams Used on Edge Only	F8	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	10000	54	4.5	10.2	-	-	-	-	-	-	-	-	26/03/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>



Wood Species: Spruce – Plies: ≥ 18 – Thickness: ≥ 35mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E11 F11	General Structural Use	F11	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	11000	55	4.0	8.7	-	11000	54.7	4.4	4.0	-	32.7	34.0	26/03/2026

Wood Species: Spruce – Plies: ≥ 18 – Thickness: ≥ 35mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E12 F14	General Structural Use	F14	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	12000	55	4.0	8.7	-	12000	54.7	4.4	4.0	-	32.7	34.0	26/03/2026

Wood Species: Spruce – Plies: ≥ 23 – Thickness: ≥ 45mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E13.2 F14	General Beams Used on Edge Only	F14	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	13200	61	4.4	9.6	-	-	-	-	-	-	-	-	26/03/2026

Wood Species: Larch – Plies: ≥ 23 – Thickness: ≥ 45mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E13.2 F14	General Structural Use	F14	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	13200	72.7	5.3	10.9	-	13200	67.8	5.3	8.7	-	35.8	41.8	26/03/2026

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmcert.com.au/>



Wood Species: Larch – Plies: ≥ 23 – Thickness: ≥ 45mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E14 F17	General Structural Use	F17	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	14500	72.7	5.3	10.9	-	14500	67.8	5.3	8.7	-	35.8	41.8	26/03/2026

Wood Species: Spruce – Plies: ≥ 15 – Thickness: ≥ 45mm – Width: ≥ 90mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E14 F17	General Beams Used on Edge Only	F17	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	14000	54.5	4.5	10.1	-	-	-	-	-	-	-	-	26/03/2026

Wood Species: Larch – Plies: ≥ 18 – Thickness: ≥ 35mm – Width: ≥ 70mm																				
Brand	Model	Use	F-Grade	Bond Type	Adhesive	Treatment	Emission Class	On Edge E [MPa]	On Edge $f'_b$ [MPa]	On Edge $f'_s$ [MPa]	On Edge $f'_\rho$ [MPa]	On Edge $f'_{sj}$ [MPa]	On Flat E [MPa]	On Flat $f'_b$ [MPa]	On Flat $f'_s$ [MPa]	On Flat $f'_\rho$ [MPa]	On Flat $f'_{sj}$ [MPa]	Axial $f'_t$ [MPa]	Axial $f'_c$ [MPa]	Date Endorsed
NordinPine	E16 F22	General Structural Use	F22	A	Phenolic Formaldehyde Resin	-	Super E <sub>0</sub>	16000	78.1	7.4	10.9	-	16000	74.2	6.5	8.7	-	43.6	48.6	26/03/2026

**End of Record**

**Certificate No:** PC10237

**Originally Certified:** 26/03/2026

**Updated:** 26/03/2026

**Expires:** 26/03/2031

- The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document and may only be reproduced in its entirety. For further information contact the certificate holder. Nothing in this certificate should be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.
- It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website <https://register.cmicert.com.au/>

