



# Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

**Precision Flow Solutions**

4/185 Briens Road, Northmead, NSW 2152, Australia

ABN: 81 144 394 531

W: [www.hydrosystemsco.com](http://www.hydrosystemsco.com)

T: +612 9625 8122

**Subject to the following conditions and limitations:**

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3.
3. Nothing in this document should be construed as a warranty or guarantee by CMI Certification (CMI), and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland

**CMI Certification Pty Ltd**

PO Box 273, Palmwoods, Qld 4555,

Australia

ABN: 81 663 250 815

T: + 61 7 5445 2199

W: [www.cmcert.com.au](http://www.cmcert.com.au)

E: [office@cmcert.com.au](mailto:office@cmcert.com.au)



080045	27/03/2019	08/04/2024	27/03/2029	WMTS-101:2021 Appliances (low hazard rating)
--------	------------	------------	------------	--

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
--------------------	----------------------------	----------------------------	---------------------------	-----------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website [www.abcb.gov.au](http://www.abcb.gov.au)





# Schedule To

APPLICABLE STANDARD/SPECIFICATION

WMTS-101:2021 Appliances (low hazard rating)



Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No/Not Applicable	Date Endorsed
Hydro	Teat Spray Sani	SPF0025	Chemical Dispenser - Eductor PID Dual feed 1 outlet	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.            Not for the supply of Drinking Water.            Minimum Inlet Pressure: 206 kPa.            Maximum Inlet Pressure: 586 kPa.            Maximum Water Temp: 48°C.            Inlet Size: 20mm BSP            Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	AccuPro	SP7xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.            Not for the supply of Drinking Water.            Minimum Inlet Pressure: 206 kPa.            Maximum Inlet Pressure: 586 kPa.            Maximum Water Temp: 48°C.            Inlet Size: 20mm BSP            Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	AccuPro	SP7xxAG	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.            Not for the supply of Drinking Water.            Minimum Inlet Pressure: 206 kPa.            Maximum Inlet Pressure: 586 kPa.            Maximum Water Temp: 48°C.            Inlet Size: 20mm BSP            Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	Penguin Pro	SP7xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.            Not for the supply of Drinking Water.            Minimum Inlet Pressure: 172 kPa.</p>	N/A	27/03/2019

				<p>Maximum Inlet Pressure: 414 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>		
Hydro	Penguin Pro	SP7012	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 172 kPa.  Maximum Inlet Pressure: 414 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	Penguin Pro	SP7013	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 172 kPa.  Maximum Inlet Pressure: 414 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	Penguin 4U	SP69xx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	Penguin 4U	SP6996	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	Penguin 4U	SP6997	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.</p>	N/A	08/04/2024

				<p>Minimum Inlet Pressure: 172 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>		
Hydro	Penguin 4U	SP68xx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	Penguin 4U	SP6883	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	AccuDose DF	SP5702	Chemical Dispenser - Eductor dual feed PID 1 outlet	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	StreamLine	8xxxAG-2	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	StreamLine	8xxxEG	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.</p>	N/A	08/04/2024

				<p>Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>		
Hydro	StreamLine	8xxx1	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	StreamLine	83xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	StreamLine	84xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	StreamLine	85xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	StreamLine	86xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.</p>	N/A	08/04/2024

				<p>Not for the supply of Drinking Water.  Minimum Inlet Pressure: 172 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>		
Hydro	AccuMax QDV	35xxx	Chemical Dispenser - Eductor PID with 1 to 2 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	25/07/2022
Hydro	AccuMax QDV	35221	Chemical Dispenser - Eductor PID with 1 to 2 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	AccuMax QDV	35231	Chemical Dispenser - Eductor PID with 1 to 2 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	AccuMax QDV	35241	Chemical Dispenser - Eductor PID with 1 to 2 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	MiniDose	683xx	Chemical Dispenser - Eductor PID with single outlet	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.</p>	N/A	27/03/2019

				<p>Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>		
Hydro	MiniDose	112601	Chemical Dispenser - Eductor PID with single outlet	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	MiniDose	112603	Chemical Dispenser - Eductor PID with single outlet	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	AccuPro	39xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	AccuPro	39301	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.  Not for the supply of Drinking Water.  Minimum Inlet Pressure: 206 kPa.  Maximum Inlet Pressure: 586 kPa.  Maximum Water Temp: 48°C.  Inlet Size: 20mm BSP  Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024

Hydro	AccuPro	39331	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.          Not for the supply of Drinking Water.          Minimum Inlet Pressure: 206 kPa.          Maximum Inlet Pressure: 586 kPa.          Maximum Water Temp: 48°C.          Inlet Size: 20mm BSP          Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	AccuPro	39761	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.          Not for the supply of Drinking Water.          Minimum Inlet Pressure: 206 kPa.          Maximum Inlet Pressure: 586 kPa.          Maximum Water Temp: 48°C.          Inlet Size: 20mm BSP          Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	08/04/2024
Hydro	AccuPro	39xxAG	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.          Not for the supply of Drinking Water.          Minimum Inlet Pressure: 206 kPa.          Maximum Inlet Pressure: 586 kPa.          Maximum Water Temp: 48°C.          Inlet Size: 20mm BSP          Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	AccuMax	35xxx	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.          Not for the supply of Drinking Water.          Minimum Inlet Pressure: 206 kPa.          Maximum Inlet Pressure: 586 kPa.          Maximum Water Temp: 48°C.          Inlet Size: 20mm BSP          Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3</p>	N/A	27/03/2019
Hydro	AccuMax	35xxxAG	Chemical Dispenser - Eductor PID with 1 to 4 outlets	<p>Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device.          Not for the supply of Drinking Water.          Minimum Inlet Pressure: 206 kPa.          Maximum Inlet Pressure: 586 kPa.          Maximum Water Temp: 48°C.          Inlet Size: 20mm BSP</p>	N/A	27/03/2019



				Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3		
Hydro	SinkMaster	8831	Chemical Dispenser - Eductor PID with 1 to 2 outlets	Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device. Not for the supply of Drinking Water. Minimum Inlet Pressure: 172 kPa. Maximum Inlet Pressure: 586 kPa. Maximum Water Temp: 48°C. Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3	N/A	27/03/2019
Hydro	SinkMaster	886	Chemical Dispenser - Eductor PID with 1 to 2 outlets	Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device. Not for the supply of Drinking Water. Minimum Inlet Pressure: 172 kPa. Maximum Inlet Pressure: 586 kPa. Maximum Water Temp: 48°C. Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3	N/A	08/04/2024
Hydro	SinkMaster	883	Chemical Dispenser - Eductor PID with 1 to 2 outlets	Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device. Not for the supply of Drinking Water. Minimum Inlet Pressure: 206 kPa. Maximum Inlet Pressure: 586 kPa. Maximum Water Temp: 48°C. Inlet Size: 20mm BSP Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3	N/A	27/03/2019
Hydro	SinkMaster	886AG	Chemical Dispenser - Eductor PID with 1 to 2 outlets	Wall mounted Chemical Dispenser with a low risk of back siphonage integral air-gap backflow prevention device. Not for the supply of Drinking Water. Minimum Inlet Pressure: 206 kPa. Maximum Inlet Pressure: 586 kPa. Maximum Water Temp: 48°C. Inlet Size: 20mm BSP Must be installed in accordance with the current version of the Plumbing Code of Australia and requirements of S41C1 of NCC 2022 Volume 3	N/A	08/04/2024

\*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record