

CERTIFICATE OF CONFORMITY

This is to certify that

Shenzhen Hongtai Doors & Windows Co., Ltd

Is certified to manufacture products to:

AS 2047:2014 Windows and external glazed doors in buildings

Certificate Holder

Shenzhen Hongtai Doors & Windows Co., Ltd

201-B, Building B2, Zone B,Phase I, Baoneng Science and Technology Park (South Zone), Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong, 518000, China Ph: +86 13802583737

W: www.windows-china.com

Certification Body



CMI Certification Pty Ltd ABN: 81 663 250 815

JAS-ANZ Accreditation No. Z4450210AK PO Box 273, Palmwoods Qld 4555, Australia

Ph: +61 7 5445 2199

E: office@cmicert.com.au
W: https://cmicert.com.au/

Product Description

Aluminium Windows and External Glazed Doors

Product Purpose or Use

Aluminium Windows and Doors for residential and commercial housing


Subject to the following Conditions & Limitations:

Nil

Certificate No: TT10060/PC10060

Originally Certified: 18/12/2020 **Updated:** 21/03/2023 **Expires:** 18/12/2025

Talissa Ireland
CMI Certification Pty Ltd



[•] It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website https://register.cmicert.com.au/





CERTIFICATE OF CONFORMITY

This is to certify that

Shenzhen Hongtai Doors & Windows Co., Ltd

Is certified to manufacture products to:

AS 2047:2014 Windows and external glazed doors in buildings

Model Identification	Product	Product Description	Performance	Date Endorsed
HT102	Awning Window	Aluminium Frame:2700mm (Width) x 2700 mm (Height) x 102 mm (Thickness). Glass:5mm + 12A + 5mm tempered double glazing safety glass to AS/NZS 2208:1996	Serviceability Limit Wind Pressure: 800Pa Ultimate Limit Wind Pressure: 3000Pa Water Penetration Resistance: 450Pa	18/12/2020
HT102	Sliding Door	Aluminium Frame:3300 mm (Width) x 2700 mm (Height) x 102 mm (Thickness). Glass:5mm + 12A + 5mm tempered double glazing safety glass to AS/NZS 2208:1996	Serviceability Limit Wind Pressure: 800Pa Ultimate Limit Wind Pressure: 3000Pa Water Penetration Resistance: 300Pa	18/12/2020
HT102	Casement Door	Aluminium Frame:900mm (Width) x 2400 mm (Height) x 102 mm (Thickness). Glass:6mm + 12A + 6mm tempered double glazing safety glass to AS/NZS 2208:1996	Serviceability Limit Wind Pressure: 1600Pa Ultimate Limit Wind Pressure: 4000Pa Water Penetration Resistance: 450Pa	18/12/2020
HT76	Awning Window	Aluminium Frame:2700 mm (Width) x2700 mm (Height) x 76 mm (Thickness). Glass:5mm + 9A + 5mm tempered double glazing safety glass to AS/NZS 2208:1996	Serviceability Limit Wind Pressure: 800Pa Ultimate Limit Wind Pressure: 2000Pa Water Penetration Resistance: 450Pa	18/12/2020

End of Record



[•] The Certificate is issued to and relates to the certification of the described product(s) to the requirements of the described relevant Standard(s) and is subject to the conditions and limitations as described hereupon. CMI Certification Pty Ltd (CMI) is an Accredited Product Certification Body and undertakes certification in accordance with ISO/IEC 17065. The CMI ProdCert Scheme is an ISO/IEC 17067 Type 5 Scheme applicable to products seeking to show conformity to a particular Standard. This certification is to be read, considered and used as a whole document. For futher information contact the certificate holder. Nothing in this certificate bould be construed as a warranty or guarantee by CMI, and the only applicable warranties or guarantees will be those provided by the Certificate Holder. CMI by granting this certification shall have no responsibility or liability for infringement of, any patent or other proprietary right.

[•] It is advised to check that this Certificate is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the CMI website https://register.cmicert.com.au/