



WaterMark

Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Xiamen Galenpoo Kitchen & Bathroom Technology Co., Ltd

No. 1, Huli Industrial Park, Mei Xi Road,
Tongan District, Xiamen City, Fujian Province, China

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland
CMI Certification Pty Ltd
PO Box 273, Palmwoods, Qld 4555, Australia
ABN: 81 663 250 815
T: + 61 7 5445 2199
W: www.cmicert.com.au
E: office@cmicert.com.au



080075	13/09/2023	03/12/2025	12/09/2028	AS/NZS 3662:2005 Performance of showers for bathing
--------	------------	------------	------------	---

CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION
-----------------------	-------------------------------	-------------------------------	------------------------------	--------------------------------------

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Xiamen Galenpoo Kitchen & Bathroom Technology Co., Ltd



APPLICABLE
STANDARD/SPECIFICATION
AS/NZS 3662:2005 Performance of showers for bathing

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free*Yes/No**/Not Applicable	Date Endorsed
Tamefox; NEWSEE; Baseau; Basecn	Hand Shower	14292	Hand Shower - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa, Recommended Working Pressure: 0.1 - 0.5Mpa, Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Hand Shower	14595	Hand Shower - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Hand Shower	14691	Hand Shower - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Hand Shower	14591	Hand Shower - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Hand Shower	13251	Hand Shower - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Hand Shower	10931	Hand Shower - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Shower Head	24591	Shower Head - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Shower Head	72020	Shower Head - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Shower Head	21651	Shower Head - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023

Tamefox; NEWSEE; Baseau; Basecn	Shower Head	22712	Shower Head - ABS - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Shower Head	22912	Shower Head - ABS - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Shower Head	SS21010	Shower Head – SUS304 Stainless Steel - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn	Shower Head	SS22010	Shower Head – SUS304 Stainless Steel - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	13/09/2023
Tamefox; NEWSEE; Baseau; Basecn, LiwCho	Shower Hose	41001	Shower Hose - SUS201 Stainless Steel Flexible Hose, PA Tube	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Hand Shower	LC-14594-SS	Hand Shower – ABS Shower Head & Fittings - Flow Controller Fengshun B16-9L WM74669 - SUS201 Stainless Steel Flexible Hose, PA Tube	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Shower Combo	LC-15391-Combo	Shower Combo - SUS304 & SUS201 Stainless Steel with SUS304 Stainless Steel Shower Head & ABS Shower Head - Flow Controller Neoperl 58.8639.1 WMKA21177 - SUS201 Stainless Steel Flexible Hose, PA Tube	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Shower Combo	LC-14292-Combo	Shower Combo - SUS304 Stainless Steel with ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose, PA Tube	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Shower Combo	LC-23231-15393-Combo	Shower Combo - ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Hand Shower Head	LC-14594	Hand Shower Head – ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Hand Shower Head	LC-14391	Hand Shower Head - ABS - Flow Controller Fengshun B16-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Hand Shower Head	LC-14896	Hand Shower Head - ABS with 9L/min Flow Controller	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Shower Head	LC-22712	Shower Head – ABS - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
LiwCho	Shower Head	LC-24892	Shower Head – ABS - Flow Controller Fengshun C19-9L WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	01/02/2024
HOFOFAO	Shower Combo	S14693	Shower Combo – SUS304 Stainless Steel with ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose, PA Tube	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	27/06/2024

Tamefox, NEWSEE, Baseau, Basecn, GALENPOO	Shower Combo	BA145C10-SetA	Shower Combo – SUS304 Stainless Steel with ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Tamefox, NEWSEE, Baseau, Basecn, GALENPOO	Shower Combo	TF146C10-SetA	Shower Combo – SUS304 Stainless Steel with ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Tamefox, NEWSEE, Baseau, Basecn, GALENPOO	Shower Combo	BA145C10-SetB	Shower Combo – SUS304 Stainless Steel with ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Tamefox, NEWSEE, Baseau, Basecn, GALENPOO	Shower Combo	TF146C10-SetB	Shower Combo – SUS304 Stainless Steel with ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Tamefox, NEWSEE, Baseau, Basecn, GALENPOO	Shower Combo	BA145F12-SetC	Shower Combo – SUS304 Stainless Steel with SUS304 & ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Tamefox, NEWSEE, Baseau, Basecn, GALENPOO	Shower Combo	TF146F12-SetC	Shower Combo – SUS304 Stainless Steel with SUS304 & ABS Shower Heads - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Ngardk/GALENPOO	Shower Combo	14898	Shower Combo – ABS Shower Head - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
AUHUB, GALENPOO	Shower Combo	14896S	Shower Combo – ABS Shower Head - Flow Controller Fengshun C19-9L WM74669 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/10/2024
Kovizen	Hand Shower	14294	Hand Shower - ABS Shower Head & Fittings - Flow Controller Neoperl 58.8639.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	10/02/2025
Kovizen	Hand Shower	14592	Hand Shower - ABS Shower Head & Fittings - Flow Controller Neoperl 58.8639.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	10/02/2025
HYDRA	Shower Head	72083	Shower Head - ABS - Flow Controller Neoperl 58.8639.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	10/02/2025
GALENPOO	Shower Head	72065	Shower Head – ABS - Flow Controller Neoperl 58.8647.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	27/05/2025
AUHUB, GALENPOO	Shower Combo	AUHUB-LSFS	Shower Combo – SUS201 Stainless Steel with ABS Shower Heads - Flow Controller Neoperl 58.8639.1 WMKA21177 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	27/05/2025
Erumpere, GALENPOO	Shower Combo	Shower Head-Round	Shower Combo - ABS Shower Head - Flow Controller Neoperl 58.8647.1 WMKA21177 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	27/05/2025
Erumpere, GALENPOO	Shower Combo	Shower Head-Flower	Shower Combo - ABS Shower Head - Flow Controller Neoperl 58.8647.1 WMKA21177 - SUS201 Stainless Steel Flexible Hose	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	27/05/2025

YFUN	Hand Shower	13908	Hand Shower – ABS - Flow Controller Neoperl 58.7409.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/09/2025
AUHUB, GALENPOO	Shower Combo	SHOWERHEAD-72026	Shower Combo - ABS & SUS201 Stainless Steel Pipe - Flow Controller Neoperl 58.8647.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/09/2025
AUHUB, GALENPOO	Shower Head	SHOWERHEAD-72080	Shower Head – ABS - Flow Controller Neoperl 58.8647.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/09/2025
AUHUB, GALENPOO	Hand Shower with Shower Hose	SHOWERHEAD-17035	Hand Shower with Shower Hose – ABS & SUS304 Stainless Steel Flexible Hose - Flow Controller Neoperl 58.8647.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	15/09/2025
Tamefox	Hand Shower + Stainless Steel Hose	14595-SS	Hand Shower with Shower Hose - SUS201 Stainless Steel Shower Hose - Flow Controller Fengshun B16-9 WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
Tamefox	Hand Shower + Stainless Steel Hose and Shower Holder	14595-SH	Hand Shower with Shower Hose - ABS & SUS201 Stainless Steel Hose - Flow Controller Fengshun B16-9 WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
Tamefox	Hand Shower + Stainless Steel Hose	14691-SS	Hand Shower with Shower Hose - ABS & SUS201 Stainless Steel Hose - Flow Controller Fengshun B16-9 WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
Tamefox	Hand Shower + Stainless Steel Hose and Shower Holder	14691-SH	Hand Shower with Shower Hose - ABS & SUS201 Stainless Steel Hose - Flow Controller Fengshun B16-9 WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
Baseau	Hand Shower + Stainless Steel Hose	14591-SS	Hand Shower with Shower Hose - ABS & SUS201 Stainless Steel Hose - Flow Controller Fengshun B16-9 WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
Baseau	Hand Shower + Stainless Steel Hose and Shower Holder	14591-SH	Hand Shower with Shower Hose - ABS & SUS201 Stainless Steel Hose - Flow Controller Fengshun B16-9 WM74669	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
AUTAP, GALENPOO	Shower head - Flower with Hose	S14693	Hand Shower with Shower Hose - SUS201 Stainless Steel Shower Hose - Flow Controller Neoperl 58.8647.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025
AUTAP, GALENPOO	Shower head - Flower with Hose and Stent	S14693E06	Hand Shower with Shower Hose - SUS201 Stainless Steel Shower Hose - Flow Controller Neoperl 58.8647.1 WMKA21177	Maximum Working Pressure: 1Mpa Recommended Working Pressure: 0.1 - 0.5Mpa Maximum Hot Water Temperature: 49°C	N/A	03/12/2025

*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

End of Record