



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

Yuhuan Donghai Valve CO., LTD
Fashantou Village, Longxi Town,
Yuhuan City, Zhejiang, China 317609

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
 2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
 3. Nothing in this document should be construed as a warranty or guarantee by CMI Certification (CMI), and the only applicable warranties will be those provided by the Certificate Holder.
1. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland
CMI Certification Pty Ltd
PO Box 273, Palmwoods, Qld 4555, Australia
ABN: 81 663 250 815
T: + 61 7 5445 2199
W: www.cmicert.com.au
E: office@cmicert.com.au



080085	15/04/2024	01/05/2026	30/04/2028	AS 3688:2016 Water supply and gas systems – Metallic fittings and end connectors
CERTIFICATE NUMBER	INITIAL CERTIFICATION DATE	CURRENT CERTIFICATION DATE	CERTIFICATION EXPIRY DATE	APPLICABLE STANDARD/SPECIFICATION

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

Yuhuan Donghai Valve Co., Ltd



APPLICABLE STANDARD/SPECIFICATION
AS 3688:2016 Water supply and gas systems – Metallic fittings and end connectors

Brand Name	Model Name	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
DONG HAI	STRAIGHT COUPLING	DHA-J3601-1	STRAIGHT COUPLING 16mm x 16mm – Push Fit Fitting - DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STRAIGHT COUPLING	DHA-J3601-2	STRAIGHT COUPLING 20mm x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STRAIGHT COUPLING	DHA-J3601-3	STRAIGHT COUPLING 25mm x 25mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STRAIGHT COUPLING	DHA-JC3601-6	STRAIGHT COUPLING DN15 (1/2" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STRAIGHT COUPLING	DHA-JC3601-7	STRAIGHT COUPLING DN20 (3/4" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STRAIGHT COUPLING	DHA-J3601-4	STRAIGHT COUPLING 12mm x 12mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	STRAIGHT COUPLING	DHA-J3601-5	STRAIGHT COUPLING 15mm x 15mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. COUPLING	DHA-J3602-1	RED. COUPLING 20mm x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. COUPLING	DHA-J3602-2	RED. COUPLING 25mm x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. COUPLING	DHA-JC3602-4	RED. COUPLING 16mm x DN15 (1/2" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. COUPLING	DHA-JC3602-5	RED. COUPLING 20mm x DN20 (3/4" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. COUPLING	DHA-J3602-3	RED. COUPLING 12mm x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-1	MALE CONNECTOR 16mm x 15mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-4	MALE CONNECTOR 20mm x 20mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	MALE CONNECTOR	DHA-J3603-7	MALE CONNECTOR 25mm x 25mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-2	MALE CONNECTOR 16mm x 20mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-3	MALE CONNECTOR 20mm x 15mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-6	MALE CONNECTOR 25mm x 20mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-JC3603-12	MALE CONNECTOR DN15 (1/2" COPPER) x 15mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-JC3603-13	MALE CONNECTOR DN20 (3/4" COPPER) x 20mm MI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-8	MALE CONNECTOR 12mm x 3/8" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-9	MALE CONNECTOR 12mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	MALE CONNECTOR	DHA-J3603-10	MALE CONNECTOR 12mm x 3/4" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CONNECTOR	DHA-J3603-11	MALE CONNECTOR 15mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-1	FEMALE CONNECTOR 16mm x 15mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-3	FEMALE CONNECTOR 20mm x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-4	FEMALE CONNECTOR 25mm x 25mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-2	FEMALE CONNECTOR 16mm x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-JC3604-9	FEMALE CONNECTOR DN15 (1/2" COPPER) x 15mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-JC3604-10	FEMALE CONNECTOR DN20 (3/4" COPPER) x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	FEMALE CONNECTOR	DHA-J3604-5	FEMALE CONNECTOR 12mm x 3/8"F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-6	FEMALE CONNECTOR 12mm x 1/2"F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-7	FEMALE CONNECTOR 12mm x 3/4" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE CONNECTOR	DHA-J3604-8	FEMALE CONNECTOR 15mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ELBOW	DHA-J3605-1	ELBOW 16mm x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ELBOW	DHA-J3605-2	ELBOW 20mm x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ELBOW	DHA-J3605-3	ELBOW 25mm x 25mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ELBOW	DHA-JC3605-6	ELBOW DN15 (1/2" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	ELBOW	DHA-JC3605-7	ELBOW DN20 (3/4" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ELBOW	DHA-J3605-4	ELBOW 12mm x 12mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ELBOW	DHA-J3605-5	ELBOW 15mm x 15mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE ELBOW	DHA-J3607-1	MALE ELBOW 16mm x R1/2"-15 – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE ELBOW	DHA-J3607-2	MALE ELBOW 20mm x R3/4"- 20 – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE ELBOW	DHA-J3607-3	MALE ELBOW 12mm x 3/8" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE ELBOW	DHA-J3607-4	MALE ELBOW 12mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE ELBOW	DHA-J3607-5	MALE ELBOW 15mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	FEMALE ELBOW	DHA-J3608-1	FEMALE ELBOW 16mm x R1/2"-15 – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE ELBOW	DHA-J3608-2	FEMALE ELBOW 20mm x G3/4"-20 – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE ELBOW	DHA-J3608-3	FEMALE ELBOW 12mm x 3/8" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE ELBOW	DHA-J3608-4	FEMALE ELBOW 12mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE ELBOW	DHA-J3608-5	FEMALE ELBOW 15mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	TEE	DHA-J3609-1	TEE 16mm x 16mm x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	TEE	DHA-J3609-2	TEE 20mm x 20mm x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	TEE	DHA-J3609-3	TEE 25mm x 25mm x 25mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	TEE	DHA-JC3609-6	TEE DN15 (1/2" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	TEE	DHA-JC3609-7	TEE DN20 (3/4" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	TEE	DHA-J3609-4	TEE 12mm x 12mm x 12mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	TEE	DHA-J3609-5	TEE 15mm x 15mm x 15mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. TEE	DHA-J3610-1	RED. TEE 20mm x 20mm x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. TEE	DHA-J3610-4	RED. TEE 25mm x 25mm x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. TEE	DHA-J3610-2	RED. TEE 20mm x 16mm x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	RED. TEE	DHA-J3610-3	RED. TEE 20mm x 16mm x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	RED. TEE	DHA-J3610-5	RED. TEE 16mm x 16mm x 12mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ST. TAP CONNECTOR	DHA-J3612-1	ST. TAP CONNECTOR 16mm x 15mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ST. TAP CONNECTOR	DHA-J3612-2	ST. TAP CONNECTOR 20mm x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ST. TAP CONNECTOR	DHA-J3612-3	ST. TAP CONNECTOR 12mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	ST. TAP CONNECTOR	DHA-J3612-4	ST. TAP CONNECTOR 15mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BENT TAP CONNECTOR	DHA-J3613-1	BENT TAP CONNECTOR 16mm x 15mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BENT TAP CONNECTOR	DHA-J3613-2	BENT TAP CONNECTOR 20mm x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BENT TAP CONNECTOR	DHA-J3613-3	BENT TAP CONNECTOR 12mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	BENT TAP CONNECTOR	DHA-J3613-4	BENT TAP CONNECTOR 15mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-J3614-1	STOP END 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-J3614-2	STOP END 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-J3614-3	STOP END 25mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-JC3614-6	STOP END DN15 (1/2" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-JC3614-7	STOP END DN20 (3/4" COPPER) – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-J3614-4	STOP END 12mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	STOP END	DHA-J3614-5	STOP END 15mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	BP ELBOW	DHA-J3616-1	BP ELBOW 16mm x 15mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP ELBOW	DHA-J3616-2	BP ELBOW 20mm x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP ELBOW	DHA-JC3616-6	BP ELBOW DN15 (1/2" COPPER) x 15mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP ELBOW	DHA-JC3616-7	BP ELBOW DN20 (3/4" COPPER) x 20mm FI – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP ELBOW	DHA-J3616-3	BP ELBOW 12mm x 3/8" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP ELBOW	DHA-J3616-4	BP ELBOW 12mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP ELBOW	DHA-J3616-5	BP ELBOW 15mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	PE-X / FLARE ADP	DHA-J3625-1	PE-X / FLARE ADP. 16mm x 15mm FLARE – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	PE-X / FLARE ADP	DHA-J3625-2	PE-X / FLARE ADP. 20mm x 20mm FLARE – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-1	BP. ELBOW 16mm x 15mm MI x 75mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-2	BP. ELBOW 16mm x 15mm MI x 100mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-3	BP. ELBOW 16mm x 15mm MI x 185mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-4	BP. ELBOW 20mm x 20mm MI x 200mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-5	BP. ELBOW 16mm x 1/2" M x 95mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-6	BP. ELBOW 16mm x 1/2" M x 130mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BP. ELBOW	DHA-J3626-7	BP. ELBOW 20mm x 3/4" M x 95mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	BP. ELBOW	DHA-J3626-8	BP. ELBOW 20mm x 3/4" M x 130mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	CONV. UNION	DHA-JC3635-1	CONV. UNION 16mm x DN15 Cu – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	CONV. UNION	DHA-JC3635-2	CONV. UNION 20mm x DN20 Cu – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	CONV. UNION	DHA-JC3636-1	CONV. UNION 16mm SDR9 PEX x 16mm SDR7.4 PEX – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	CONV. UNION	DHA-JC3636-2	CONV. UNION 20mm SDR9 PEX x 20mm SDR7.4 PEX – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	CONV. ELBOW	DHA-JC3637-1	CONV. ELBOW 16mm x DN15 Cu – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	CONV. ELBOW	DHA-JC3637-2	CONV. ELBOW 20mm x DN20 Cu – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	COPPER CONV. TEE	DHA-JC3638-1	COPPER CONV. TEE 16mm x 16mm x DN15 Cu – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	COPPER CONV. TEE	DHA-JC3638-2	COPPER CONV. TEE 20mm x 20mm x DN20 Cu – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	COPPER CONV. TEE	DHA-JC3638-3	COPPER CONV. TEE DN15 Cu x DN15 Cu x 16mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	COPPER CONV. TEE	DHA-JC3638-4	COPPER CONV. TEE DN20 Cu x DN20 Cu x 20mm – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	LONG ELBOW	DHA-J3627	LONG ELBOW 20 MI x 20mm OD – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	FEMALE ELBOW	DHA-J3628	FEMALE ELBOW 20mm x 1" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	BRANCH TEE	DHA-J3629	BRANCH TEE 20mm x 16mm x 1/2" F – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CENTRE TEE	DHA-J3622-1	MALE CENTRE TEE 16mm x 16mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CENTRE TEE	DHA-J3622-2	MALE CENTRE TEE 20mm x 20mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

DONG HAI	MALE CENTRE TEE	DHA-J3622-3	MALE CENTRE TEE 20mm x 20mm x 3/4" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CENTRE TEE	DHA-J3622-4	MALE CENTRE TEE 16mm x 16mm x 3/4" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CENTRE TEE	DHA-J3622-5	MALE CENTRE TEE 12mm x 12mm x 3/8" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CENTRE TEE	DHA-J3622-6	MALE CENTRE TEE 12mm x 12mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024
DONG HAI	MALE CENTRE TEE	DHA-J3622-7	MALE CENTRE TEE 14mm x 14mm x 1/2" M – Push Fit Fitting – DR Brass	For Cold & Hot Water Use Only Maximum Temperature: 95°C Maximum Operating Pressure: 1.6 MPa Fittings for use with copper tube, stainless steel pipe, stainless steel tube and adaptor fittings for connection to other pipe materials in water supply systems	No	15/04/2024

*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

** Product is not Lead Free compliant

End of Record