



Certificate of Conformity

THIS CERTIFICATE IS GRANTED TO

YUHUAN XINBAODA METAL PRODUCTS CO., LTD

Building 1, No. 1 Shuangtai Road,
Pharmaceutical Packaging Industrial Park,
Lupu Town, Yuhuan City, Taizhou City,
Zhejiang Province, 317600, China

Subject to the following conditions and limitations:

1. The Approved Certifier grants the right to use or arrange the use of the WaterMark as shown in the top left corner only in respect of the Products described and detailed on the Product Schedule following which are produced by the Approved User and which comply with the appropriate Applicable Specification referenced below and as amended from time to time. The Licence is granted subject to the rules governing the use of the WaterMark and the terms and conditions for certification. The WaterMark Licensee covenants to comply with all the Rules, technical reference documents and terms and conditions of the WaterMark Certification Scheme.
2. The Certified products must be installed in accordance with the current version of the Plumbing Code of Australia.
3. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate Holder.
4. Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but CMI Certification Pty Ltd (CMI) shall have no responsibility or liability for results obtained or damages resulting from such use. CMI grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by CMI, and the only applicable warranties will be those provided by the Certificate holder.

Talissa Ireland
CMI Certification Pty Ltd
PO Box 273, Palmwoods, Qld 4555, Australia
ABN: 81 663 250 815
T: + 61 7 5445 2199
W: <https://cmicert.com.au>
E: office@cmicert.com.au



080097

14/02/2025

14/02/2025

13/02/2030

AS/NZS 2537.2:2011 Mechanical jointing fittings for use with crosslinked polyethylene (PE-X), Part 2: Plastics piping systems for hot and cold water installations – crosslinked polyethylene (PE-X) – Fittings (ISO 15875-3:2003, MOD)

**CERTIFICATE
NUMBER**

**INITIAL
CERTIFICATION DATE**

**CURRENT
CERTIFICATION DATE**

**CERTIFICATION
EXPIRY DATE**

**APPLICABLE
STANDARD/SPECIFICATION**

This Certificate is issued by a JAS-ANZ accredited certification body. The Scheme Owner, Administering Body and Accreditation Body do not in any way warrant, guarantee or represent that the product the subject of this Certificate conforms to the WaterMark Certification Scheme Rules, nor accepts any liability arising out of the use of the product. The Scheme Owner disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

The WaterMark is a registered certification trademark of the Scheme Owner (ABN 74 599 608 295). The rules of the WaterMark Certification Scheme are available from the ABCB website www.abcb.gov.au





Schedule To

YUHUAN XINBAODA METAL PRODUCTS CO., LTD



APPLICABLE
STANDARD/SPECIFICATION
AS/NZS 2537.2:2011 Mechanical jointing fittings for use with crosslinked polyethylene (PE-X), Part 2:
Plastics piping systems for hot and cold water installations – crosslinked polyethylene (PE-X) –
Fittings (ISO 15875-3:2003, MOD)

Brand Name	Model	Model Identification	Product Description	Scope of Use	Lead Free* Yes/No**/Not Applicable	Date Endorsed
XINBAODA	PUSH FIT	ADBF-C 0101	STRAIGHT COUPLING 16mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C - Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0102	STRAIGHT COUPLING 20mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0103	STRAIGHT COUPLING 25mm x 25mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0104	STRAIGHT COUPLING DN15 (1/2" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0105	STRAIGHT COUPLING DN20 (3/4" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0106	STRAIGHT COUPLING 12mm x 12mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 0101	STRAIGHT COUPLING 15mm x 15mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0201	RED. COUPLING 20mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0203	RED. COUPLING 25mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0204	RED. COUPLING 16mm x DN15 (1/2" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0205	RED. COUPLING 20mm x DN20 (3/4" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0206	RED. COUPLING 12mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0301	MALE CONNECTOR 16mm x 15mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

XINBAODA	PUSH FIT	ADBF-C 0302	MALE CONNECTOR 20mm x 20mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0304	MALE CONNECTOR 25mm x 25mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0305	MALE CONNECTOR 16mm x 20mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0306	MALE CONNECTOR 20mm x 15mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0307	MALE CONNECTOR 25mm x 20mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0308	MALE CONNECTOR DN15 (1/2" COPPER) x 15mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0309	MALE CONNECTOR DN20 (3/4" COPPER) x 20mm MI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0310	MALE CONNECTOR 12mm x 3/8"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0311	MALE CONNECTOR 12mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0317	MALE CONNECTOR 12mm x 3/4"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 0301	MALE CONNECTOR 15mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0401	FEMALE CONNECTOR 16mm x 15mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0402	FEMALE CONNECTOR 20mm x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0404	FEMALE CONNECTOR 25mm x 25mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0405	FEMALE CONNECTOR 16mm x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C0408	FEMALE CONNECTOR DN15 (1/2" COPPER) x 15mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C0409	FEMALE CONNECTOR DN20 (3/4" COPPER) x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0410	FEMALE CONNECTOR 12mm x 3/8"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0411	FEMALE CONNECTOR 12mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0417	FEMALE CONNECTOR 12mm x 3/4"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 0401	FEMALE CONNECTOR 15mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0501	ELBOW 16mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

XINBAODA	PUSH FIT	ADBF-C 0502	ELBOW 20mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0503	ELBOW 25mm x 25mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0504	ELBOW DN15 (1/2" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0505	ELBOW DN20 (3/4" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0506	ELBOW 12mm x 12mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 0501	ELBOW 15mm x 15mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0701	MALE ELBOW 16mm x R1/2"-15 – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0702	MALE ELBOW 20mm x R3/4"-20 – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0703	MALE ELBOW 25mm x R1" – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0704	MALE ELBOW 12mm x 3/8"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0705	MALE ELBOW 12mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 0701	MALE ELBOW 15mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0801	FEMALE ELBOW 16mm x G1/2"-15 – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0802	FEMALE ELBOW 20mm x G3/4"-20 – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0803	FEMALE ELBOW 25mm x G1" – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0804	FEMALE ELBOW 12mm x 3/8"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0805	FEMALE ELBOW 12mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 0801	FEMALE ELBOW 15mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1001	TEE 16mm x 16mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1002	TEE 20mm x 20mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1003	TEE 25mm x 25mm x 25mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1004	TEE DN15 (1/2" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

XINBAODA	PUSH FIT	ADBF-C 1005	TEE DN20 (3/4" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1006	TEE 12mm x 12mm x 12mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 1001	TEE 15mm x 15mm x 15mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1101	RED. TEE 20mm x 20mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1102	RED. TEE 25mm x 25mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1103	RED. TEE 20mm x 16mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1104	RED. TEE 20mm x 16mm x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1108	RED. TEE 16mm x 16mm x 12mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1106	RED. TEE 25mm x 20mm x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1107	RED. TEE 25mm x 20mm x 25mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1301	ST. TAP CONNECTOR 16mm x 15mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1302	ST. TAP CONNECTOR 20mm x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1310	ST. TAP CONNECTOR 12mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 1301	ST. TAP CONNECTOR 15mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1401	BENT TAP CONNECTOR 16mm x 15mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1402	BENT TAP CONNECTOR 20mm x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	XBDQF-G 1403	BENT TAP CONNECTOR 12mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 1401	BENT TAP CONNECTOR 15mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1501	STOP END 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1502	STOP END 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1503	STOP END 25mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1504	STOP END DN15 (1/2" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

XINBAODA	PUSH FIT	ADBF-C 1505	STOP END DN20 (3/4" COPPER) – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1506	STOP END 12mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 1501	STOP END 15mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1701	BP ELBOW 16mm x 15mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1702	BP ELBOW 20mm x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1704	BP ELBOW DN15 (1/2"COPPER) x 15mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1705	BP ELBOW DN20 (3/4"COPPER) x 20mm FI – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1706	BP ELBOW 12mm x 3/8"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1707	BP ELBOW 12mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-A 1701	BP ELBOW 15mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2201	PE-X / FLARE ADP. 16mm x 15mm FLARE – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2202	PE-X / FLARE ADP. 20mm x 20mm FLARE – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2401	BP ELBOW 16mm x 15mm MI x 75mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2402	BP ELBOW 16mm x 15mm MI x 100mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2403	BP ELBOW 16mm x 15mm MI x 185mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2404	BP ELBOW 20mm x 20mm MI x 200mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2405	BP ELBOW 16mm x 1/2"M x 95mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2406	BP ELBOW 16mm x 1/2"M x 130mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2407	BP ELBOW 20mm x 3/4"M x 95mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2408	BP ELBOW 20mm x 3/4"M x 130mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2501	CONV. UNION 16mm x DN15 Cu – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2502	CONV. UNION 20mm x DN20 Cu – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

XINBAODA	PUSH FIT	ADBF-C 0101A	CONV. UNION 16mm SDR9 PEX x 16mm SDR7.4 PEX – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0102A	CONV. UNION 20mm SDR9 PEX x 20mm SDR7.4 PEX – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0501R	CONV. ELBOW 16mm x DN15 Cu – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0502R	CONV. ELBOW 20mm x DN20 Cu – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1101A	COPPER CONV. TEE 16mm x 16mm x DN15 Cu – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1102A	COPPER CONV. TEE 20mm x 20mm x DN20 Cu – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1103A	COPPER CONV. TEE DN15 Cu x DN15 Cu x 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 1104A	COPPER CONV. TEE DN20 Cu x DN20 Cu x 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0704L	Long Elbow 20 MI x 20mm OD – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 0804L	Female Elbow 20mm x 1"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C1204	BRANCH TEE 20mm x 16mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3201	Male Centre Tee 16mm x 16mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3202	Male Centre Tee 20mm x 20mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3203	Male Centre Tee 20mm x 20mm x 3/4"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3204	Male Centre Tee 16mm x 16mm x 3/4"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3205	Male Centre Tee 12mm x 12mm x 3/8"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3206	Male Centre Tee 12mm x 12mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3207	Male Centre Tee 14mm x 14mm x 1/2"M – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2601	BREACH ASSMBLY R/A 200mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2602	BREACH ASSMBLY R/A 300mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2701	BREACH ASSEMBLY ST. 200mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2702	BREACH ASSEMBLY ST. 300mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

XINBAODA	PUSH FIT	ADBF-C 2801	BREACH RIGHT ANGLE 150mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2802	BREACH RIGHT ANGLE 200mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2901	BREACH INV. 150mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 2902	BREACH INV. 200mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3001	BATH BREACH 200mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	ADBF-C 3002	BATH BREACH 300mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C0601	45°Elbow 16mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C0602	45°Elbow 20mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C0603	45°Elbow 25mm – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1201	Female Centre Tee 16mm x 16mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1202	Female Centre Tee 20mm x 20mm x 1/2"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1203	Female Centre Tee 20mm x 20mm x 3/4"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1204	Female Centre Tee 16mm x 16mm x 3/4"F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1205	Female Centre Tee 12mm x 12mm x 3/8F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025
XINBAODA	PUSH FIT	SHQF-C1206	Female Centre Tee 12mm x 12mm x 1/2F – CW511L DR Copper Alloy Body – SUS316 Circlip – EPDM O Ring – POM Cover – Class2/10bar	Max Water Temp: 95°C Max Operating Pressure: 1.6MPa	No	14/02/2025

*Lead Free compliance in accordance with NCC 2022 - Volume Three – Plumbing Code of Australia - A5G4(2)(b)

** Product is required to be Lead Free compliant by 01/05/2026

End of Record